NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

JACK 992

State Well No. 34S/1W-20b

State Permit No.

(1) OWNER:
Name TEDDIE MIX
Address PO BOX 952 SHADY COVE COVE ORE

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 40 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used TORCH
Size of perforations 1/2 in. by 1 in.
10 perforations from 25 ft. to 40 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 7 gal./min. with 155 ft. drawdown after 1 1/2 hrs.
Artesian flow g.p.m.
Temperature of water 56 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 7 sacks
How was cement grout placed? INSURTED PIPE OUTSIDE CASING PLACED CEMENT THUR PIPE UNTILL FULL PULLED PIPE OUT
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata 35, 215
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County JACKSON Driller's well number
¼ ¼ Section 20 T. 34 R. 1 W W.M.
Bearing and distance from section or subdivision corner
300 WEST 300 NW CORNER OF SECTION 20

(11) WATER LEVEL: Completed well.
Depth at which water was first found 35 ft.
Static level 60 ft. below land surface. Date NOV 5/79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 220 ft. Depth of completed well 220 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
CLAY STONE WHITE	0	35	35
CLAY MEDIUM GRAY	35	190	
ROCK MEDIUM + SHALE	190	220	
GRAY BLUE	220		

RECEIVED
FEB 14 1980
WATER RESOURCES DEPT.
SALEM, OREGON

Work started OCT 10 1979 Completed NOV 5 1979
Date well drilling machine moved off of well NOV 5 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] U.V. Howlett (Drilling Machine Operator) Date NOV 5, 1978
Drilling Machine Operator's License No. 135

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name U.V. HOWLETT WELL DRILLING (Person, firm or corporation) (Type or print)
Address 3535 CRATER LAKE HWY MED
[Signed] U.V. Howlett (Water Well Contractor)
Contractor's License No. 332 Date NOV 10, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

JACK 992

RECEIVED NOV 26 1979 WATER RESOURCES DEPT SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 34S/1W-20b
State Permit No. OBSOLETE FORM

(1) OWNER:
Name TEDDIE MIX
Address PO BOX 952 SHADY COVE ORE

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 40 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used X
Size of perforations 1/2 in. by 1 in.
10 perforations from 25 ft. to 40 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 7 gal./min. with 155 ft. drawdown after 1 1/2 hrs.
Artesian flow g.p.m. 155A
Temperature of water 56 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 7 sacks
Number of sacks of bentonite used in well seal NON sacks
X How was cement placed?
~~Brand name of bentonite~~
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata 35, 215
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County JACKSON Driller's well number
¼ ¼ Section 20 T. 34 R. 1W W.M.
Bearing and distance from section or subdivision corner
300 WEST 300 NW CORNER SECTION 20

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 60 ft. below land surface. Date NO X
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 220 ft. Depth of completed well 220 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
CLAY STONE WHIT	0	35	35
CLAY MED. HD GRAY	35	190	
ROCK MED. HD. GRAY	190	220	
ROCK BLUE HD SHALE	270		

Work started OCT 10 1979 Completed NOV 5 1979
Date well drilling machine moved off of well NOV 5 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] U.V. Howlett (Drilling Machine Operator) Date NOV 14, 1979
Drilling Machine Operator's License No. 135

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name U.V. HOWLETT WELL DRILLING (Person, firm or corporation) (Type or print)
Address 3835 CRATER LAKE HWY MED ORE
[Signed] U.V. Howlett (Water Well Contractor)
Contractor's License No. 332 Date NOV 10, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119