## WATER WELL REPORT STATE OF OREGON



## RECEIVED State Well No. 95/15E 29 APR 2 2 1983 State Process

PLEASE TYPE OWNTERINGESOURCES DEPT.

3		/
•	State Permit No.	
t	PERT	

	SALEM, OREGON
(1) OWNER:	(10) LOCATION OF WELL:
Name William Rueter	County Jefferson Driller's well number
Address 25106 116th Avenue S.E.	4 4 Section 29 T. 9S R. 15E W.M
City Kent State 0Wash. 98	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: none assigned
New Well   Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found 200 ft
(3) TYPE OF WELL: (4) PROPOSED USE (check)	Static level 42 ft. below land surface. Date 3 -28-8.
•	Artesian pressure lbs. per square inch. Date
Rotary Mud	(12) WELL LOG: Diameter of well below casing
	Depth drilled 225 ft. Depth of completed well 225 ft
5) CASING INSTALLED: Steel F Plastic Threaded Welded F	Formation: Describe color, texture, grain size and structure of materials; and show
10 "Diam from +1 ft to 196 ft Gauge .250	thickness and nature of each attention and equifor nonetrated with at least one section
" Diam. from	to teach change of formacion report each change in position of Static water neve
LINER INSTALLED:	MATERIAL From To SWL
(C) PERSONAL TRANS	Sand & Gravel 22 50
(6) PERFORATIONS: Perforated? ☐ Yes 💥 No Type of perforator used	Blue Clay 50 163
Size of perforations in. by in.	Yellow Clay 163 192
	Red Sand & Gravels, Water-Rear 192 225 42
perforations from ft. to	
perforations from tt. to perforations from tt. to	
	1.10
(7) SCREENS: Well screen installed? ☐ Yes X☐ No	
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to Slot Size Se	
Drawdown is amount water level is lowered	.10.
(8) WELL TESTS: below static level	
s a pump test made? Y Yes No If yes, by whom? Contractor	
.eld: 250 gal/min. with 20 ft. drawdown after 72	hrs.
	"
Air test gal./min. with drill stem at ft.	hrs.
Bailer test gal./min. with ft. drawdown after	nrs.
esian flow g.p.m.	
unperature of water 54* Depth artesian flow encountered	. ft. Work started 8-25 19 82 Completed 3-28 19 83
(9) CONSTRUCTION: Special standards: Yes □ No 🗷	Date well drilling machine moved off of well 3-28 19 83
Well seal—Material used Cement	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to20	
Diameter of well bore to bottom of seal14 in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal 10" in.	[Signed] Date 4-6 , 19 83
Number of sacks of cement used in well seal	Bonded water wen constructor certification.
How was cement grout placed? Pressure Grouted	Bond 630130021279 Issued by: U.S. Fidelity & Guarant: Surety Company Name
	This well was drilled under my jurisdiction and this report is true to
Was pump installed? Yes Type Subm. Hr. 25 Depth 200	the best of my knowledge and belief.
Was a drive shoe used?   Yes □ No Plugs Size: location	Person firm or corporation of The or project
Did any strata contain unusable water?  Yes  No	Address 1686 N.E. Negus Way, Redmond, Oreg. 9775
Type of Water? depth of strata	
Method of sealing strata off	[Signet] Water Well Constructor
Was well gravel packed? ☐ Yes 👿 No Size of gravel:	Date
Gravel placed from ft. to ft.	