

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT RECEIVED

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print) DEC 10 1974

State Well No. 7517E-6ab

State Permit No. Jeff 203

WELL #1
66878

(1) OWNER:

Name BOB MORSS
Address BOX 15 ANTELOPE, OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

(4) PROPOSED USE (check):

Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other stock
Dug Bored

(5) CASING INSTALLED:

Threaded Welded
8" Diam. from + 1 ft. to 20 ft. Gage 250
6" Diam. from + 1 ft. to 259 ft. Gage 141

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used torch
Size of perforations 1/8 in. by 12 in.
40 perforations from 120 ft. to 140 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Baller test 30 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 60 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 10 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Jefferson Driller's well number
3/4 NE 1/4 Section 6 T. 9S R. 17E W.M.
Bearing and distance from section or subdivision corner 1980' W
& 1320' S of NE corner Sec 6

(11) WATER LEVEL: Completed well.

Depth at which water was first found 128 ft.
Static level 128 ft. below land surface. Date 11/18-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8

Depth drilled 270 ft. Depth of completed well 270 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
black soil	0	2	
bldrs & congl	2	9	
rhyolite	9	65	
brown sandstone	65	80	
yellow sandstone & clay (WB)	80	135	
green clay	135	185	
green clay stone (water)	185	270	128

Work started 11/1 1974 Completed 11/18 1974
Date well drilling machine moved off of well 11/18 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Wayne Mester Date 12/4 1974
(Drilling Machine Operator)
Drilling Machine Operator's License No. 969

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Crawford Well Drilling (Person, firm or corporation) (Type or print)
Address 3626 N.W. Coyner Redmond, Ore 97756
[Signed] Dale Crawford (Water Well Contractor)
Contractor's License No. 451 Date 12/04 1974