

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

*Jeff
325*

WATER WELL REPORT

RECEIVED

STATE OF OREGON AUG 5 1981 State Well No. _____

(Please type or print) WATER RESOURCES DEPT. State Permit No. _____
SALEM, OREGON

(1) OWNER:

Name Homestead Investment Co.
Address 1204 Chestnut St.
Madras, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
8" Diam. from +1 ft. to 122 ft. Gage .250
6" Diam. from 110 ft. to 250 ft. Gage .188
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.
Type of perforator used cutting torch
Size of perforations 1/4 in. by 6 in.
480 perforations from 123 ft. to 182 ft.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: 52 gal./min. with total ft. drawdown after 1 1/2 hrs.
" " " " " "
" " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water _____ Depth artesian flow encountered _____ ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 18 sacks
How was cement grout placed? pumped
Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(10) LOCATION OF WELL:

County Jefferson Driller's well number D-226-79
S.E. 1/4 S.W. 1/4 Section 6 T. 10S R. 13E W.M. _____
Bearing and distance from section or subdivision corner _____

(11) WATER LEVEL: Completed well.

Depth at which water was first found 123 ft.
Static level 80 ft. below land surface. Date 5-10-79
Artesian pressure _____ lbs. per square inch. Date _____

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 250 ft. Depth of completed well 250 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
topsoil	0	3	
brown clay	3	68	
blue clay	68	84	
claystone gray	84	123	
rock-decomp-clay-water	123	182	80
gray claystone	182	218	
brownish blue clay	218	250	

Work started 5-2 1979 Completed 5-10 1979
Date well drilling machine moved off of well 5-10 1979

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] David Donnelly Date 5-11, 1979
(Drilling Machine Operator)
Drilling Machine Operator's License No. 883

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name S. & M. Drilling & Supply, Inc.
(Person, firm or corporation) (Type or print)
Address 399 S.E. Walnut, Canby, Oregon 97013
[Signed] Walter Mac
(Water Well Contractor)
Contractor's License No. 497 Date 5-11, 1979