NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
FEB 18 1975
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 10S/14E-27
State Permit No.

Jeff 362

(1) OWNER:
Name GARY KNUTSS
Address 4255 TERRA LINDA DR
ALBANY ORE 97321

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other State ☐

) CASING INSTALLED:
Threaded ☐ Welded ☒
5/8" Diam. from 0 ft. to 25 1/2 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

) PERFORATIONS:
Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: 200 gal./min. with NO ft. drawdown after 2 1/2 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 25 1/2 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 5 in.
Number of sacks of cement used in well seal 3 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County JOFF Driller's well number
¼ ¼ Section 27 T. 10S R. 14 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 344 ft.
Static level 344 ft. below land surface. Date 12-22-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 5
Depth drilled 405 ft. Depth of completed well 405 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
OVER BURDEN	0	3	
SOFT BROWN SANDSTONE	3	23	
SOFT LAVA	23	40	
HARD LAVA	40	55	
SOFT SANDSTONE	55	344	
WATER BEARING SAND	344	405	344

Work started 12-24 19 74 Completed 12-27 19 74
Date well drilling machine moved off of well 12-27 19 74

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Thomas Jackson Date 12-27, 19 74
(Drilling Machine Operator)
Drilling Machine Operator's License No. 320

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name (Person, firm or corporation) (Type or print)
Address
[Signed] (Water Well Contractor)
Contractor's License No. Date , 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119