NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)



State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Darrell Friend	County Jefferson Driller's well number 157-A	
Address Box 41	NE 1/4 NE 1/4 Section 36 T. 98 R.16E v	W.M.
Ashwood, OR 97711	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon Standard Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20	ft.
Rotary X Driven D Domestic D Industrial Municipal D	Static level 25 ft. below land surface. Date	
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
75) CASING INSTALLED: Threaded Welded Welded Search	(12) WELL LOG: Diameter of well below casing 8 Depth drilled 125 ft. Depth of completed well 125 Formation: Describe color, texture, grain size and structure of mater and show thickness and nature of each stratum and aquifer penetra with at least one entry for each change of formation. Report each change position of Static Water Level and indicate principal water-bearing str	ated. ge in
rype of perforator used	MATERIAL From To SW	几
Size of perforations in. by in.	Top Soil - Brown 0 1	
perforations from ft. to ft.	Clay & Sand - Brown 1 6	
perforations from ft. to ft.	Clay - Brown 6 20	
perforations from ft. to ft.	Sand & Gravel - Clay-Brown20 25	
(7) SCREENS: Well screen installed? Yes No	Rock - Broken - Grey 25 80 25 (Water Bearing)	—
Manufacturer's Name	Rock - Green & Blue 80 125	—
Type Model No	4.0 4.1 0.0 1.2 1.0 1.2 1.0 1.2 1.2 1.0 1.2 1.2 1.0 1.0 1.2 1.0 1.0 1.2 1.0 1.0 1.0 1.	
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? X Yes No If yes, by whom? Driller		
acid: 25 gal./min. with 0 ft. drawdown after 1 hrs.		
" " "		
- n n n		—
Baller test gal./min. with ft. drawdown after hrs.		
esian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started 12-3 19 79 Completed 12-3 19	79
(9) CONSTRUCTION:		79
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision Materials used and information reported above are true to	
Diameter of well hore to bottom of seal	best knowledge and belief.	•
Diameter of well bore below seal 8 in.	[Signed] Date 1-2, 19	80
Number of sacks of cement used in well seal 10 sacks	Drilling Machine Operator's License No. 1075	
How was cement grout placed? Mixed up with 6 gal. water to 1 sack of sement - placed from		
bottom up,	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Rod's Well Drilling, Inc. (Person, firm or corporation) (Type or print)	
Did any strata contain unusable water? Yes No	PO DOY SEL PRIDATELA DE	
Type of water? depth of strata	Address 10 20 7 7	
Method of sealing strata off	[Signed] Molling College	
Was well gravel packed? ☐ Yes 🛣 No Size of gravel:	(Water Well Contractor)	0.0
Gravel placed from ft. to ft.	Contractor's License No. 663 Date 1-2 , 19.	<u></u> O