WATER WELL REPORT STATE OF OREGON

JEFF

APR 2 3 1981

RECEIVED

State Well No.

1/5/5=1/26

493

WATER RESOURCES DERTate Permit No.
SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name Marybrooke Corporation	County Jefferson Driller's well number			
Address Star Route	NW ¼ SW ¼ Section 11 T. 118		5E _{w.m}	
City Ashwood, State Ore. 9771		Sub	division	
(2) TYPE OF WORK (check):	Address at well location: Same			
New Well ☑ Deepening □ Reconditioning □ Abandon □	*****			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	vell.		
	Depth at which water was first found	6	ft	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 20 ft. below	land surface.	. Date 2-9-81	
Rotary Air X Driven Domestic Dindustrial Municipal Rotary Mud X Dug Dirrigation X Test Well Dother	1 The obstant problem of the state of the st	Artesian pressure lbs. per square inch. Date		
Rotary Mud X Dug	(12) WELL LOG: Diameter of well below casing			
) CASING INSTALLED: Steel 🕱 Plastic 🗆	Depth drilled 256 ft. Depth o	f completed w	vell 256 ft	
18 "Diam. from +1½ ft. to —38½ ft. Gauge	Formation: Describe color, texture, grain size and stithickness and nature of each stratum and aquifer pen for each change of formation. Report each change in and indicate principal water-bearing strata.	etrated, with	n at least one entry	
LINER INSTALLED:		 		
	MATERIAL	From	To SWL	
16 "Diam from +1 ft to 256 ft Gauge •250		+	80 4	
(6) PERFORATIONS: Perforated?	Rock, Grn., Red & Black	+	.00 4	
Type of perforator used Factory	Rock, Lt. Brwn., Solid		.05 4 .30 4	
Size of perforations 1/8 in. by 3 in.	Rock, Multi-colored, soft		33	
5760 perforations from 136 t. to 256	Rock, Solid		.45 8	
perforations from ft. to	Rock, Brwn & Red Variegated		.50 12'	
perforations from ft. to	Rock		.53 20'	
(7) SCREENS: Well screen installed? ☐ Yes 🗷 No	Rock, Red		.62 "	
Manufacturer's Name	Rock, Multi-colored		.72 "	
Type Model No.	Mocks Hard Offi Oray Scone		75 "	
Diam. Slot Size Set from ft, to				
Diam. Slot Size Set from ft. to	MOCK! MULCI COLOTER		.70	
Drawdown is amount water level is lowered	_ <u>nata drin page yaw</u>		.23	
(8) WELL TESTS: below static level below the description of the static level is lowered below the static level	Dk-Grey-Hard Claystone Rock	225 2	256 "	
Was a pump test made? DKYes D No If yes, by whom? A & H Pump S	erv.			
d: 1300 gal./min. with 120 ft. drawdown after 8 hr		 		
" "		+		
Air test gal./min. with drill stem at ft. hi		+		
Bailer test gal./min. with ft. drawdown after hi	8.	+		
^→esian flow g.p.m.		+		
perature of water 55% Depth artesian flow encountered	Work started 10-18 1980 Complete	1.2-0	19 81	
(a) CONSTRUCTION.	Work started 10-18 19 80 Completed 2-9 19 81 Date well drilling machine moved off of well 2-9 19 81			
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \) \(\text{X} \)			19 0	
Well seal—Material used Cement Well sealed from land surface to 35	Drilling Machine Operator's Certification:			
TOTAL COURT OF THE CONTROL OF THE CO	This well was constructed under my direct			
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief. [Signed]			
68	Prilling Machine Operator)		,, 19.01	
Transfer of Science of Control and the Control of Control and Control of Cont	Drilling Machine Operator's License No. 967			
How was cement grout placed? Pumped	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is true to			
Was nump installed? 10 m III D. II	the best of my knowledge and belief.			
Was pump installed?	Name Orvail Buckner Well Drilling, Inc.			
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location	(Person, firm or corporation) (Type or print)			
Type of Water? surface depth of strata 6°	Address 1686 N.E. Negus Way Rec	mond	7EG - 3//30	
Method of sealing strata off casing & grout	- Signed Chuar Lie	ep	~	
Was well gravel packed? ☐ Yes No Size of gravel:	- (Water Well Contrac		01	
Dize of graves.	- Contractor's License No. 608 Date 2-9	!	19.81	