NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date

WATER WELL RÉPORT

STATE OF OREGON

(Please type or print)

JEFE.		Well No. 135/8E-26b
Comme 1	State	Well No. 100 000
592	State	Permit No

of well completion. (Do not write a	bove this line)		,	
(1) OWNER:	(10) LOCATION OF WELL:			
Name U.S.D.A. Ferest Service	County 3007 County Driller's well number			
Address 211 NE Dovero	SW 14 WW 14 Section 26 T. 138 'R. 8 B W.M			
Dend. Cro. 97701	Bearing and distance from section or subdivis			** . 112
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivis	100 COLUE	<u>:r</u>	
New Well ■ Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) THATTEN FEMALES OF 1 4 1	11		***
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed v	vell.		
Potony P Dwisson D	Depth at which water was first found 27			ft
/ e	Static level 30 ft. below land	surface.	Date 11	-23-79
L_6 Bored I Irrigation Test Well Other	Artesian pressure lbs. per squa	re inch.	Date	
Threaded Welded	(12) WELL LOG: Diameter of well			^
10 "Diam from 1 ft. to 20 ft. Gage 250	Signification went		Z 93	
9" Diam. from				ft
6 " Diam. from 6 ft. to 67 ft. Gage .250	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and struc im and a	ture of: auifer n	materials enetrated
) DEDEODATIONS.	with at least one entry for each change of forms	ation. Rep	ort each	change in
) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	acipal wa	ter-beari	ing strata
Type of perforations in hy 12 in	MATERIAL	From	То	SWL
Size of perforations 4 III. by	hrom sandy sail	0	3	
perforations fromft. toft.	brum coarse conditions	3	27	<u> </u>
perforations from ft. to ft.	fine send & gravel VB	27	41	30
perforations from ft. to ft.	brown coarse contains	41	50	
(7) SCREENS: Well screen installed? Yes I No	coarse black send & gravel VB	50	67	
Manufacturer's Name		 		-
Type Model No		 		
Diam. Slot size Set from ft. to ft.		-		
Diam. Slot size Set from ft. to ft.		1		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level control a pump test made? Yes No If yes, by whom?				
Yield: 80 gal./min. with 1 ft. drawdown after 4 hrs.	V			
" " "				
" " "				
•				
test gal./min. with ft. drawdown after hrs.		L		
an flow g.p.m.				
nperature of water Depth artesian flow encountered ft.	Work started 11-15 19 79 Complete		11-2	2 19 7 9
(9) CONSTRUCTION:	Date well drilling machine moved off of well		11-26	19
Well seal—Material used	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my			
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above a	ire true	to my
Diameter of well bore below seal in.		Date	11-29	10 75
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	02	//	., 10
How was cement grout placed?	Drilling Machine Operator's License No.	7.43	7	•••••
	Water Well Contractor's Cartifications			
	Water Well Contractor's Certification:	-4.	3 43 1	
	This well was drilled under my jurisditrue to the best of my knowledge and beli	ction an ief.	a this r	eport is
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Granfand Well Drilling. 1	Me.		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Ту	pe or prir	_ `
Type of water? depth of strata 14 R.	Address 1275 Lever Bridge Vay To	Tropp	me, (Æ.
Method of sealing strata off 8 1nch cooling & concent	[Signed] garry K. Grandon	nd		
Was well gravel packed? [Yes No Size of gravel:	(Water Well Control			
Gravel placed from ft. to ft.	Contractor's License No Date	1	1-29	., ₁₉ .79