WATER WELL REPORT STATE OF OREGON

PLEASE TYPE or PRIN

SEP 2 1 1983

•	
State Permit No.	

AT INNESCURCES	Marie Articles of Marie San	
ALZM. OF	÷	,

(1) OWNER:	(10) LOCATION OF WELL:		
Name Deschutes National Forest	County Jefferson Driller's well		
Address211 E. Revere	SW 14 NE 14 Section 3 T. 13S	R. 9E	W.M.
City Bend 9770/ State OR	Tax Lot # Lot Blk	Subdivision	1
(2) TYPE OF WORK (check):	Address at well location: Allingham well	-	
New Well			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 4		ft.
	Static level 6 ft. below l	and surface. Date	9/12/8
Rotary Air	Artesian pressure lbs. pe	er square inch. Date	<u> </u>
□ Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below	casing 8	
) CASING INSTALLED: Steel X Plastic -	Depth drilled 57 ft. Depth of	completed well 5	7 ft.
Threaded Welded	Formation: Describe color, texture, grain size and structure thickness and nature of each stratum and aquifer pene		
8 "Diam. from 2 ft. to -22 ft. Gauge .250	for each change of formation. Report each change in		
	and indicate principal water-bearing strata.		
LINER INSTALLED:	MATERIAL	From To	SWL
	topsoil	0 4	
(6) PERFORATIONS: Perforated? □ Yes X No	coarse gravel WB	4 16	6
Type of perforator used	grey hard rock	16 22	
Size of perforations in. by in.	grey hard broken rock WB	22 57	
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft		 	
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
Type			
Diam. Slot Size Set from ft. to ft.			
Diam. Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
" s a pump test made? XYes □ No If yes, by whom? A & H Pump			
eld: 40 gal./min. with 29 ft. drawdown after 5 hrs			
<i>II</i> , , , , , , , , , , , , , , , , , ,			
Air test gal./min. with drill stem at ft. hrs			
Bailer test 18 gal./min. with 10 ft. drawdown after 1 hrs			
esian flow g.p.m.			
Imperature of water Depth artesian flow encountered ft	Work started 9/8 19 83 Complete	ed .9/9	
(9) CONSTRUCTION: Special standards: Yes \square No	Date well drilling machine moved off of well	9/12	19 8
Well seal—Material used Cement	(unbonded) Water Well Constructor Certifi	ication (if appli	icable):
Well sealed from land surface to	This well was constructed under my direct s		
Diameter of well bore to bottom of sealin.	and information reported above are true to my b		
Diameter of well bore below sealin.	[Signed]	. Date	., 19
Number of sacks of cement used in well seal 23 sacks	bonded water well constructor certificati	ion:	
How was cement grout placed? pressure grout		rn Surety ety Company Name	
	This well was drilled under my jurisdiction		is true to
W	the best of my knowledge and belief.	_	
Was pump installed? Type HP Depth ft	1 (41110		or print)
Was a drive shoe used? ☐ Yes X No Did any strata contain unusable water? ☐ Yes ☐ No	Address 1245 Lower Bridge Terre	bonne, OR	or prints
Type of Water? surface depth of strata 4 to -16	9 10 1	_ 0	
Method of sealing strata off Cemented off	[Signed]	tor	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Date	9/19	, 19. 83
Gravel placed from ft. to ft.			