NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED FEB 26 1979 WATER RESOURCES DEPT. SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Corrected 2-23-79
JEFF
728

State Well No. 13S/14E-10a
State Permit No.

(1) OWNER:
Name Andy Morrow
Address 1240 Chestnut Madras, Ore 97741

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☐ Jetted ☒
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☒
10" Diam. from 0 ft. to 160 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☒ Yes ☐ No.
Type of perforator used Cutting torch
Size of perforations 1/8 in. by 6 in.
540 perforations from 60 ft. to 160 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type None Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 50 gal./min. with 5 ft. drawdown after 1 hrs.
Artesian flow None g.p.m.
Temperature of water 56° Depth artesian flow encountered None ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? Bentonite was poured dry down around the casing
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 1/4 minus
Gravel placed from 20 ft. to 160 ft.

(10) LOCATION OF WELL:
County Jefferson Driller's well number 5232
SW ¼ NE ¼ Section 10 T. 13S R. 14E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 95 ft.
Static level 90 ft. below land surface. Date 7/21/78
Artesian pressure none lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 10"
Depth drilled 160 ft. Depth of completed well 160 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	2	
Broken rock; clay	2	15	
Sandy clay	15	95	
Coarse sand (water bearing)	95	160	90

Work started 7/20 1978 Completed 7/21 1978
Date well drilling machine moved off of well 7/21 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Archie Fox (Drilling Machine Operator) Date 2/23 1979
Drilling Machine Operator's License No. 389

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Archie Fox Well Drilling (Person, firm or corporation) (Typewr print)
Address Rt. 3 Box 202 Prineville, Ore 97754
[Signed] Archie Fox (Water Well Contractor)
Contractor's License No. 444 Date 2-23, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED JUL 24 1978 WATER RESOURCES DEPT. SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Jeff 728

State Well No. 13S/14E-10CC
State Permit No.

(1) OWNER:
Name Andy Monroe
Address 1246 Chestnut Madras, Or

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from 0 ft. to 160 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used cutting torch
Size of perforations 1/8 in. by 6 in.
540 perforations from 60 ft. to 160 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name None
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" " "
Bailer test 50 gal./min. with 3 ft. drawdown after 1 hrs.
Artesian flow none g.p.m.
Temperature of water 56° Depth artesian flow encountered none ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 12 in.
Number of sacks of ~~cement~~ Bentonite used in well seal 6 sacks
How was ~~cement~~ grout placed? Bentonite was poured dry down around the casing
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 1/4 minus
Gravel placed from 20 ft. to 160 ft.

(10) LOCATION OF WELL:
County Jefferson Driller's well number 522
SW ¼ NE ¼ Section 10 T. 13S R. 14E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 95 ft.
Static level 90 ft. below land surface. Date 7/21/78
Artesian pressure none lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 160 ft. Depth of completed well 160 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	2	
Broken rock & clay	2	15	
Sandy clay	15	95	
Coarse sand (water bearing)	95	160	90

Work started 7/20 1978 Completed 7/21 1978
Date well drilling machine moved off of well 7/21 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Archie Fox (Drilling Machine Operator) Date 7/21, 1978
Drilling Machine Operator's License No. 389

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Archie Fox, Well Drilling (Person, firm or corporation) (Type or print)
Address Rt. 3 Box 202 Prineville, Ore 97754
[Signed] Archie Fox (Water Well Contractor)
Contractor's License No. 444 Date 7/21, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119