NOTICE TO WATER WELL CONTRACTOR The original and first copy

Was well gravel packed?

Yes No

Gravel placed from ft. to ft.

WATER WELL REPORT ECEIVED

filed with the STATE OF	OREGON MAR 1 / 107 (State Well No	
STATE ENGINEER, SALEM, OREGON 973 EF (Please type	The second secon	
	STATE ENGINEER Permit No.	
of well completion. (Do not write ab	STATE ENGINEER Permit No. SALEM, OREGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Harald Buckner	County Driller's well number	
Address Kt Box 46 Juniform Orang	5W 1/4 5 1/4 Section 23 T. 13 R. 14	W.M
	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL Completed small	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	^
	Depth at which water was first found	ft
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal	Static level ft. below land surface. Date	4,8/
Dug	Artesian pressure lbs. per square inch. Date	1
CASING INSTALLED: Threaded Welded		,
	(12) WELL LOG: Diameter of well below casing	
16 "Diam from 10 ft to 20 ft Gage 2.52	Depth drilled $\mathcal{Q}_{\mathcal{C}}$ ft. Depth of completed well $\mathcal{Q}_{\mathcal{C}}$	C ft
14" Diam. from D.C. ft. to 200 ft. Gage 2.11	Formation: Describe color, texture, grain size and structure of m	aterials
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer per	
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each consistion of Static Water Level and indicate principal water-bearing	
Type of perforator used	MATERIAL From To	SWL
Size of perforations in. by in.	Jon Sail 10	01
ft. to 200 ft.	GRACIT NOW	60
perforations from ft. to ft.	Acres ferricos for	65
perforations from ft. to ft.	8: 138 Martin 70	40
(7) SCREENS: Well screen installed? Yes No	A CONTRACTOR OF THE PROPERTY O	<u> </u>
Manufacturer's Name	Charter Congression (120)	7/3
Type Model No	Sark Free 1/5	20
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
	Conditional	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Ves No If yes, by whom? Pallin' Pung	200 ft.	
eld: 3000 gal./min. with ft. drawdown after hrs.		
" " "		
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
tesian flow g.p.m.		
erature of water 4 L Depth artesian flow encountered ft.	Work started 19/6 Completed Q 15.	1960
	Date well drilling machine moved off of well	10
(9) CONSTRUCTION:	Date well drilling machine moved orr of well	-340
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct superv	
Diameter of well bore to bottom of seal	Materials used and information reported above are true best knowledge and belief.	to my
Diameter of well bore below seal in.	- Ka / 6	19.6
Number of sacks of cement used in well seal sacks	(drying machine operator)	المراسع
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this re	port is
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Typg or print	t)
	Address Da III Result Occurs B	il
	P	1
Method of sealing strata off	[Signed] Duckerice	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)	

Size of gravel: .