

RECEIVED

SEP 25 1980

State Well No. 395/5w-5dc

WATER WELL REPORT
STATE OF OREGON

Jose
10058

WATER RESOURCES DEPT
SALEM, OREGON

State Permit No.

(1) OWNER:

Name Rich Stayton
Address 1000 Cedar Flat Rd.
City Williams State ORE.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandonment []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Air [x] Driven []
Rotary Mud [] Dug []
Cable [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal []
Irrigation [] Test Well [] Other []
Thermal: Withdrawal [] Reinjection []

(5) CASING INSTALLED:

Steel Threaded [x] Plastic Welded []

6.0" Diam. from 0 ft. to 77 ft. Gauge 250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated? [] Yes [x] No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [x] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Air test 60 gal./min. with drill stem at 160 ft. 1 hrs.
Artesian flow g.p.m.
Temperature of water 52° F Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes [] No [x]

Well seal—Material used CEMENT
Well sealed from land surface to 55 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 15 sacks
How was cement grout placed? Pumped down annular space.

Was pump installed? NO Type HP Depth ft.
Was a drive shoe used? [x] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [x] No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [x] No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County JOSEPHINE Driller's well number 54-80
S.W. ¼ S.E. ¼ Section 5 T. 39S R. 5W W.M.
Tax Lot # 240 Lot Blk Subdivision
Address at well location:

(11) WATER LEVEL: Completed well.

Depth at which water was first found 80 ft.
Static level 22 ft. below land surface. Date 9/8
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6.125"

Depth drilled 160 ft. Depth of completed well 160 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
clay & boulder	0	50	
limestone	50	70	
Granite	70	160	22

Work started 9/8 1980 Completed 9/9 1980
Date well drilling machine moved off of well 9/9 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Art Carter (Drilling Machine Operator) Date 9/22, 1980
Drilling Machine Operator's License No. 997

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name ART CARTER WELL DRILLING (Person, firm or corporation) (Type of print)
Address 240 Johnson Rd. J.ville, Or.
[Signed] Art Carter (Water Well Contractor)
Contractor's License No. 597 Date 9/22, 1980

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion. SP*12658-690