KFRFIAED

WATER WELL REPORT STATE OF OREGON

JAN301981
WATER RESOURCES DEPT
SALEM, OREGON

State Well No.	355-6w-25	6-c
----------------	-----------	-----

State Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:		
Name FRED OCKENDEN	County JOSEPHINE Driller's well	number	
Address 5941 HIGHIAND AVE	5W 4 NW 4 Section 25 T. 35	R. 6w	W.M.
City GRANTS PASS State ORE	Tax Lot # Lot Blk	Subdi	
(2) TYPE OF WORK (check):	Address at well location: CALIF	Ave	
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
	Depth at which water was first found	3	ft.
	Static level 13 ft. below l	and surface. D	Date 1-14-81
ry Air Driven	Artesian pressure lbs. pe	er square inch	. Date
Cable Bored Thermal: Withdrawal Reinjection B	(12) WELL LOG: Diameter of well below	anning	6
(5) CASING INSTALLED: Steel X Plastic	100	completed wel	1.5.0
(5) CASING INSTALLED: Steel Plastic Welded Welded Z50	Formation: Describe color, texture, grain size and structure thickness and nature of each stratum and aquifer pene for each change of formation. Report each change in and indicate principal water-bearing strata.	ucture of mate	erials; and show
LINER INSTALLED:	MATERIAL	From 7	To SWL
	BROWN CLAY	O	
	DROWN CIRY	0 :	2
(6) PERFORATIONS: Perforated? ☐ Yes No Type of perforator used	BROWN Clay SMALL GRAVE	5/	0
Size of perforations in. by in.	DEN CA	1 2 2	
perforations from ft. to ft.	RED CIAY	10 1	8
perforations from ft. to ft.	70	- N -	
perforations from ft. to ft.	BROWN Clay-med GEAVEL	18 3	0
(7) SCREENS: Well screen installed? □ Yes ⋈ No	Decomposed CRANITE		
Manufacturer's Name	Decomposed OBANITE	30 7	
Type Model No.	SMACC GIZAVET	30 /	0
Diam. Slot Size Set from ft. to ft.	FRACTURED TOMBSTONE	20 10	00 14
Diam. Slot Size Set from ft. to ft.	PERCIALED LONG STORE	10 11	// /
WELL TESTS: Drawdown is amount water level is lowered below static level	ABUIFER	83 /	00 256PM
Was a pump test made? ☐ Yes 🗡 No If yes, by whom?		 	
Yield: gal./min. with ft. drawdown after hrs.			
" " " "		-	
Air test 25 gal./min. with drill stem at 25 ft. 1 hrs.			
er test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
Temperature of water 50 Depth artesian flow encountered ft.	Work started /-/4 19 8/ Complete		4 19 8/
(9) CONSTRUCTION: Special standards: Yes □ No A	Date well drilling machine moved off of well	/-	14 1981
Well seal—Material used CemenT	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my direct s		Matariala
Diameter of well bore to bottom of seal	and information reported above are true to my b	est knowled	ge and belief.
Diameter of well bore below seal	[Signed] //ULPALL Z Plone		-14, 19.8
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	1-1	4-81
How was cement grout placed? RUMPED	Drilling Machine Operator's License No	!	/
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction	ı and this re	port is true to
Was pump installed?	the best of my knowledge and belief.	Tur	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name TABUIM DRILLING		(Spe or print) _
Did any strata contain unusable water? Yes No	Address 1840 Willow LN, GRA	ants F	ASS. ORE
Type of Water? depth of strata	D A A C A	ų ,	,
Method of sealing strata off	[Signed] Water Well Contract	and	_ * .
Was well gravel packed?	Contractor's License No. 2.25 Date	1-15	19.8.1
Gravel placed from ft. to ft.			,, , . .