WATER WELL REPORT STATE OF OREGON

RECEIVED

JUN 3 0 1981

9

345/5w-3/ad

WATER RESOURCES DEPT SALEM, OREGON

	State Well No.	
JOSE/	State Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:
Name Richard StrickLan Donald Penny	County Josephine Driller's well number 588
Address 2680 Jump off Juc Cn. nd	5 E 4 N E 4 Section 31 T.345 R. 5 W W.M.
City Conunts Pass State One	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: 2680 Jump of Joe Ch. Rel
New Well ☑ Deepening □ Reconditioning □ Abandon □	Grants Poss, one
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 32 ft.
	Static level 9 ft. below land surface. Date 6-26-81
Rotary Air 🙀 Driven 🗆 Domestic 🗷 Industrial 🗆 Municipal 🗀 Rotary Mud 🗆 Dug 🖂 Irrigation 🖂 Test Well 🖂 Other 🖂	Artesian pressure lbs. per square inch. Date
Cable Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing
CASING INSTALLED: Steel Plastic	Depth drilled /60 ft. Depth of completed well /60 ft.
Threaded \square Welded \square	Formation: Describe color, texture, grain size and structure of materials; and show
"Diam from O ft to 20 ft. Gauge 250	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
ft. toft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
" Diam. from	Soil 01
	yellow Clay 1 4
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No Type of perforator used	Decomposed Granite 4 14
Size of perforations in. by in.	Black , white Granite 14 32
	Black , white Granite 32 33 9
perforations fromft. toft	Fractural
perforations fromft. toft.	Black - White Grante 33 61
	Blucks white Granite 61 62 9
(7) SCREENS: Well screen installed? Yes No	Frantined 62 107
Manufacturer's Name	Black & White Grante 107 108 9
Type Model No.	Frustinul
Diam. Slot Size Set from ft. to ft. Diam. Slot Size Set from ft. to ft.	Black , white Grante 108 160
Drawdown is amount water level is lowered	
(8) WELL TESTS: below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
Arrtest 6 gal./min. with drill stem at / 38 ft. 12 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Temperature of water 550 Depth artesian flow encountered ft.	Work started 6 - 25 198/ Completed 6 - 26 198/
CONSTRUCTION: Special standards: Yes No	Date well drilling machine moved off of well 6 - 26 198/
Well seal—Material used Coment	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Unilling Machine Operator) Dates 1957
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
How was cement grout placed?	
,, , , , , , , , , , , , , , , ,	Water Well Contractor's Certification:
**************************************	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was pump installed?	Name UL a Gonting Tour Onilling
Was a drive shoe used?	(Pageon, firm or corporation) (Type or print)
Did any strata contain unusable water? ☐ Yes ► No Type of Water? depth of strata	Address 7.0. 838X 758 770000, CM
Method of sealing strata off	[Signed] R. P. Bunlington
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor)
Gravel placed from	Contractor's License No. 33 Date
Cauton parcon at Oal	<u> </u>