STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

RECEIVED

PLEASE TYPE or PRINT IN INK

NOV 0 11984

(for official use only)

(1) OWNER: Name Charles Mandeville	(10) LOCATION OF WELLES DES County JOSESALEM OREGONWAY	descr of Section	ription 5	: of
Address 220 KINCAID Rd City Williams State ORC	Township, Range,	(Range is Ea	ast or West)	, WM.
	Tax Lot 406 Lot Block Subdivision			
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)			
New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.		EMIL 10.00		
	(11) WATER LEVEL of COMPLET	red w	ET.T.	
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Air Driven Domestic Dindustrial District D	Depth at which water was first found	2 2 2	1411111	£+
Thermal:		land surfa	ce. Date	<u>′ハーフ ¹ ˙ · · · · · · · · · · · · · · · · · ·</u>
Rotary Mud Dug Irrigation Withdrawal Reinjection Other:		r square inc		<u></u>
Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well belo		6	
(5) CASING INSTALLED: Steel Threaded Threaded Welded Welded Z Some fit to fit Gauge Some fit to fit Gauge	Depth drilled /50 ft. Depth of Formation: Describe color, texture, grain size and structure and nature of each stratum and aquifer penetrated, with at formation. Report each change in position of Static Wawater-bearing strata.	of complete e of materia least one er	d well ls; and sho ntry for eac	w thickness ch change of
LINER INSTALLED: Steel Plastic Threaded Welded	MATERIAL	From	To	SWL
"Diam. fromft. toft. Gauge	BROWN CLAY	0	4	
•				
(6) PERFORATIONS: Perforated? ☐ Yes No Size of perforations in. by	BROWN CLAY medium			
perforations fromft. toft.	TO LARGE Boulders	4	23	
perforations fromft. toft.	Decree and China			
perforations from	Decomposed GRANITE SOFT FINE	23	92	
	SOFT FINE	G-2	72	
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name	TOMBSTONE GRANITE	 		
Type	VERY FIRM & FINE	92	150	16
Diam. Slot Size Set from ft. to ft.				
Diam Slot Size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	ABUIFER	112	115	20gp1
		1111	1/17	<u> </u>
Was a pump test made? Yes No If yes, by whom?	RECEIVED	141	142	<u> 309</u> p
d: 50 gal./min. with 45 ft. drawdown after hrs.				
Air test SO gal./min. with drill stem at /45ft. hrs.	OCT 0.0 1004			
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
perature of water 52 Depth artesian flow encounteredft.	GRANTS PASS, ORS.			- / / /
(9) CONSTRUCTION: Special standards: Yes \(\) No \(\)	Date work started/complet	<u> </u>	0-25	3-84/
Well seal—Material used CEMENT	-	<u> </u>		1987
Well sealed from land surface to ft.	(unbonded) Water Well Constructor Certific			
Diameter of well bore to bottom of seal in.	This well was constructed under my direct sur information reported above are true to my best kn			
Diameter of well bore below sealin.	Nike KIEDO	1/	ケーンぐ	24
Amount of sealing material sacks pounds	[Signed] TING TYEEC	. Date		, 19
How was cement grout placed?	(bonded) Water Well Constructor Certificati		- C.,	· > 0 = 11
		TERN	<u>J</u> U	KETY
Was pump installed? NO Type HP Depth ft.	On behalf of TAQUIN DEILING LNC			
Was a drive shoe used? Yes \(\subseteq \text{No} \) Plugs Size: location	(type or print name of W	ater Well Co	nstructor)	•
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction a	and this r	eport is t	rue to the
Type of Water? depth of strata	best of my knowledge and belief:			
Method of sealing strata off	(Signed) DOC Church			
Was well gravel packed? 🗌 Yes 📈 No Size of gravel:	(Dated)(Wate/Well Constructor)			
Gravel placed from ft. to ft.	(Daieu)		••••••	***************************************