WATER WELL REPORT
STATE OF OREGON

RECEIVED SEP 28 1983 WATER RESOURCES DEPT. SALEM, OREGON

RECEIVED JUN 15 1983 WATER RESOURCES DEPT. SALEM, OREGON

PLEASE TYPE or PRINT IN INK

State Well No. [redacted]

State Permit No. 375/ow-1dd

Deepening

(1) OWNER:

Name Dale Gregory

Address 4535 New Hope Rd.

City Grants Pass State Ore.

(2) TYPE OF WORK (check):

New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air ☑ Driven ☐
Rotary Mud ☐ Dug ☐
☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED: Steel ☐ Plastic ☐ Threaded ☐ Welded ☐

6" Diam. from +2 ft. to 138 ft. Gauge .025

" Diam. from ft. to ft. Gauge

LINER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS: Perforated? ☐ Yes ☑ No

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No

Manufacturer's Name

Type Model No.

Diam. Slot Size Set from ft. to ft.

Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☑ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " "

Air test 125 gal./min. with drill stem at 133 ft. 1 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 52° Depth artesian flow encountered ft.

(9) CONSTRUCTION: Special standards: Yes ☐ No ☑

Well seal—Material used cement grout

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 8 sacks

How was cement grout placed? Grout pump

Was pump installed? no Type HP Depth ft.

Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☑ No

Type of Water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☑ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Josephine Driller's well number

SE ¼ SW ¼ Section [redacted] T. 37 R. 6 W.M.

Tax Lot # 3901 Lot Blk Subdivision

Address at well location: 4535 New Hope Rd. Grants Pass, Oregon

(11) WATER LEVEL: Completed well.

Depth at which water was first found 40 ft.

Static level 20 ft. below land surface. Date 6/10/83

Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"

Depth drilled 165 ft. Depth of completed well 165 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
deepen from 160-165 ft.			
	160	165	
Granite Black + white w/ Feldspar			

Work started 6/9/83 19 Completed 6/9 1983

Date well drilling machine moved off of well 6/9 1983

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date, 19

Bonded Water Well Constructor Certification:

Bond 2B033241 (number) Issued by: Western Surety Co. (Surety Company Name)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name McClanahan Well Drilling (Person, firm or corporation) (Type or print)

Address 141 N.E. Beacon Grants Pass Ore.

[Signed] Charles B. Pelley Water Well Constructor

Date 6/10, 1983

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*45292-690