WATER WELL REPORT STATE OF OREGON

12023 12033

DEC 1 1 1984

WATER RESOURCES DEPT SALEM, OREGON

PLEASE TYPE or PRINT IN INK

State Well No	35=/5W-30U
State Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:
Name Vic Surroz	County Oscobine Driller's well number
Address Level Donaldson Road	SE 45W 4 Section 30-3 T. 355 R. 5W W.M.
City Grants 1985 State OR	Tax Lot # 100 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: Same
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 100 ft.
	Static level and Surface ft. below land surface. Date 7-30
Rotary Air Driven	Artesian pressure lbs. per square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
CASING INSTALLED: Steel Plastic	Depth drilled ft. Depth of completed well 206 ft.
Threaded □ Welded Z	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
6. "Diam from 1. ft. to 44 ft. Gauge 250	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
"Diam. from	
LINER INSTALLED:	MATERIAL From To SWL
" Diam. from	Crushed Rock 0 3
(6) PERFORATIONS: Perforated? ☐ Yes S No	DIDWA SOIL LOVE
Type of perforator used	Brown Clay Small Gravel 6 14
Size of perforations in. by in.	Brown Clay Small Gravel 6 14 Rep Soil Small Boulders 14 60
perforations from ft. to ft.	Lava Black Boulders 60 94
perforations fromft. toft.	Granit BED Rock 94 206
perforations fromft. toft.	
(7) SCREENS: Well screen installed? ☐ Yes No	
Manufacturer's Name	
Type Model No. Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
Drawdown is amount water lavel is lawared	
(8) WELL TESTS:	
Was a pump test made? Yes No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
Air test 30 + gal./min. with drill stem at 80 ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs. Astesian flow g.p.m.	
Agressian flow g.p.m. Apperature of water Depth artesian flow encountered ft.	7-27 CU DI DIE
(A) CONCEDITORION	Work started 7-27 1984 Completed 1984
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \) Well seal—Material used	Date well drilling machine moved off of well 1984
Well sealed from land surface to 30 ft.	(unbonded) Water Well Constructor Certification (if applicable): This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal in.	and information reported above are prue to my best knowledge and belief.
Diameter of well bore below seal	[Signed]
Number of sacks of cement used in well seal sacks	Bonded Water Well Constructor Certification:
How was cement grout placed? Sluvky Lunp	Bond Issued by:
	(number) Surety Company Name This well was drilled under my jurisdiction and this report is true to
	the best of my knowledge and belief.
Was pump installed? N.D. Type HP Depth ft.	Name(Person, firm or corporation) (Type or print)
Was a drive shoe used? Yes \sum No Plugs Size: location ft. Did any strata contain unusable water? \sum Yes \sum No	Address VIC DIRDEAL VARIAGE AND ADDRESS AN
Type of Water? depth of strata	Address VIC DURDEN WELL DRILLING, INC.
Method of sealing strata off	[Signed] 5545 Riverbanks Rd., 470 41 22 Constitution 97526 CO-15
Was well gravel packed? ☐ Yes No Size of gravel:	Date 97526 10-15 1904
Gravel placed from ft. to ft.	