

JOSE
12080

355/6W-2d

STATE OF OREGON
WATER WELL REPORT
(as required by ORS 537.765)

OCT 24 1985

WATER RESOURCE: DEPT
PLEASE TYPE OR PRINT IN INK

Well # 2 SALEM, OREGON County Permit # 792 (for official use only)

(1) OWNER:

Name MOR & MRS SNOOK
Address 322 N School House Bk Rd
City GRANTS PASS State ORE

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary Air ☒ Driven ☐ Domestic ☒ Industrial ☐ Municipal ☐
Rotary Mud ☐ Dug ☐ Thermal: ☐ Withdrawal ☐ Reinjection ☐
Cable ☐ Bored ☐ Other: ☐ Piezometric ☐ Grounding ☐ Test ☐

(5) CASING INSTALLED: Steel ☒ Plastic ☐
Threaded ☐ Welded ☒
6" Diam. from 11 ft. to 24 ft. Gauge 2.50
" Diam. from ft. to ft. Gauge

LINER INSTALLED: Steel ☐ Plastic ☐
Threaded ☐ Welded ☐
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Air test 10 gal./min. with drill stem at 99 ft. hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 55° Depth artesian flow encountered ft.

(9) CONSTRUCTION: Special standards: Yes ☐ No ☒
Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6.578 in.
Amount of sealing material 9 1/2 sacks ☒ pounds ☐
How was cement grout placed? GROUT pump

Was pump installed? No Type HP Depth ft.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County Josephine 1/4 SE 1/4 of Section 2 of
Township 35S, Range 6, WM.
(Township is North or South) (Range is East or West)

Tax Lot 1301 Lot Block Subdivision

MAILING ADDRESS OF WELL (or nearest address)

SAME

(11) WATER LEVEL OF COMPLETED WELL:

Depth at which water was first found 20 ft.

Static level 16 ft. below land surface. Date 10-4-85

Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"

Depth drilled 100 ft. Depth of completed well 100 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Light Brown clay & GRANIT	0	5	
Yellow Brown clay & GRANIT	5	15	
Hard Brown decomposed GRANIT	15	95	16'
Blue Gray Rock	95	100	16'

Date work started 10-4-85 /completed 10-4-85

Date well drilling machine moved off of well 10-4 1985

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date, 19

(bonded) Water Well Constructor Certification:

Bond 13-0130-930-74 issued by U.S. Fidelity & Guaranty Co.
(number) (Surety Company Name)

On behalf of Charles K. W. Tcher
(type or print name of Water Well Constructor)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

(Signed) Charles K. W. Tcher
(Water Well Constructor)

(Dated) 10-22-85

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP*46866-690