RECEIVED

STATE OF OREGON

OCT 3 0 1985

WATER WELL REPORT
(as required by ORS 537.765) WATER RESOURCEASDIFFE or PRINT IN INK

CALEM ODECOM	or raintraction and a second s	(for official use only)	*************
(1) OWNER:	(10) LOCATION OF WELL by legs	al description:	
Name BONNIE BAKER	County JOSEPHINE SE 1/3 SW1/2	of Section	of
Address FALLING LEAF DR	Township 385 Range	8	or _, WM.
City CAUE JUNCTION State OR	(Township is North or South)	(Range is East or West)	-, ** 171.
	Tax Lot 500 Lot Block Subdivision _		
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)	AME -	
New Well 🗵 Deepening 🗆 Reconditioning 🗆 Abandon 🗆			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLE	TED WELL:	
Rotary Air - Driven Domestic Municipal Domestic Municipal D	Depth at which water was first found	12	ft.
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 27' ft. below land surface. Date 10 4/8		
Cable	Artesian pressure lbs. pe	er square inch. Date	
Cante Li Bored Li Plezometric Li Grounding Li Test	(12) WELL LOG: Diameter of well belo	. 1-41	
CASING INSTALLED: Steel Plastic	1	ow casingof completed well	ft.
CASING INSTALLED: Steel Plastic Threaded Welded	Formation: Describe color, texture, grain size and structur	e of materials; and show thi	ickness
Legar Diam. from + 1 ft. to 95 ft. Gauge 250	and nature of each stratum and aquifer penetrated, with at	least one entry for each ch	ange of
ft. To Gauge	formation. Report each change in position of Static Wawater-bearing strata.	iter Level and indicate pr	incipal
LINER INSTALLED: Steel		T	
-	MATERIAL		WL
ft. Gauge	BROWN CLAY	0 19	
(6) PERFORATIONS: Perforated? ⊠ Yes □ No	700 012 01012 01	+0 1/2	
Size of perforations 3/16 in. by 6 in.	BROWN CLAY SMALL	19 42	
60 perforations from 75 ft. to 95 ft.	GRAVEL	110 50	
perforations from	BROWN CLAY LO GRAVEL	42 72	
perforations from			
	BUTE GRADEL BUTE CLAY	72 98	
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name	BLUE CLAY BLUE GRAVEL	80188	
TypeModel No			
Diam Slot Size Set from ft. to ft.	BEDROCK	108 110 2	<u>'7</u>
Diam Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered	RECEIVED		
Delow static level	NECEI V Laboratoria		
Was a pump test made? 🗌 Yes 🔀 No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.	OCT 28 1985		
U U H	001 20 1303		
Air test 8 gal./min. with drill stem at 95 ft. hrs.			
Bailer test gal./min. with ft. drawdown after hrs.	WM. DIST. 14 GRANTS PASS, ORE		
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.			
9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date work started 1014/85 /complet	ed 1015185	
9) CONSTRUCTION: Special standards: Yes □ No 图 Well seal—Material used CEMENT GROUT	Date well drilling machine moved off of well	5 85 19	,
Well sealed from land surface toft.	(unbonded) Water Well Constructor Certific		,
٠	This well was constructed under my direct sup		
Diameter of well bore to bottom of seal	information reported above are true to my best kn	owledge and belief.	uu
		_	
Amount of sealing material sacks pounds	[Signed]	Date, 19 .	
How was cement grout placed?	(bonded) Water Well Constructor Certificati		
And the state of t	Bond 464-3690 Issued by: 15756	-0N	
120 -	(Surety Company Name)		
Vas pump installed? Type HP Depth ft.	On behalf of LEROY (type or print name of W	ater Well Constructor)	
Vas a drive shoe used? X Yes \(\subseteq \) No \(Plugs		•	
Did any strata contain unusable water?	This well was drilled under my jurisdiction a	nd this report is true t	o the
'ype of Water? depth of strata	best of my knowledge and belief:		
Method of sealing strata off	(Signed)		***********
Vas well gravel packed? ☐ Yes ☒ No Size of gravel:	Water Well Construct	or)	
Gravel placed from ft. to ft.	(Dated)		*****