WATER WELL REPORT

STATE OF OREGON



SEP 14 1981

RECEIVED

WATER RESOURCES DEPT SALEM, OREGON

State Well No. 35s	16w-23bb
--------------------	----------

State Permit No.

OWNER:	(10) LOCATION OF WELL:		
ame PARADISE RADCH	County OSEPHINE Driller's well number		
ddress 7000 MONUMENT DR	NW 4 NW 4 Section 23 T.355 R. 6 W	W.M.	
ity PRANTS PASS State ORE	Tax Lot # 1600 Lot Blk Subdivision	1	
2) TYPE OF WORK (check):	Address at well location: SAME		
Tew Well	(11) WATER LEVEL: Completed well.		
abandonment, describe material and procedure in Item 12.	Depth at which water was first found 102	ft.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 33 ft. below land surface. Date	<u> 7-15-81</u>	
otary Air Driven Domestic Andustrial Municipal Otal	Artesian pressure lbs. per square inch. Dat	te //	
otary Mud	(12) WELL LOG: Diameter of well below casing		
	Depth drilled 200 ft. Depth of completed well		
5) CASING INSTALLED: Steel Plastic Threaded Welded Welded	Formation: Describe color, texture, grain size and structure of material	s; and show	
8 "Diam from 0 ft to 14 ft. Gauge	thickness and nature of each stratum and aquifer penetrated, with at lea for each change of formation. Report each change in position of Static	Water Level	
"Diam from ft to ft. Gauge	and indicate principal water-bearing strata.		
LINER INSTALLED:	MATERIAL From To	SWL	
	BRI) (1 Ay.		
"Diam. from ft. to ft. Gauge	COURSE SAND 0 140	33	
6) PERFORATIONS: Perforated? Le Yes No			
Type of perforator used, TORCH	ROCK - BLK & WHITE 140 200	133	
lize of perforations III. by			
65 perforations from 133 ft. to 143 ft.			
perforations from		<u> </u>	
perforations from			
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
Type Model No			
Diam. Slot Size Set from ft. to ft.		-	
Diam. Slot Size Set from ft. to ft. Drawdown is amount water level is lowered			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes No If yes, by whom?			
gal./min. with ft. drawdown after hrs.			
" 100 " 200 " 1 "			
Air test 80 gal./min. with drill stem at 200t. 2 hrs.			
Bailes test 60 gal/min. with 200t. drawdown after 3 hrs.			
Amerian flow g.p.m.		ــــــــــــــــــــــــــــــــــــــ	
Depth artesian flow encountered ft.	Work started	<u>5 19 8</u>	
(9) CONSTRUCTION: Special standards: Yes □ No	Date well drilling machine moved off of well	19 8	
Well seal—Material used YORTZAND CEMEUT	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my direct supervision. Ma	aterials use	
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge	/ 7 to S	
Diameter of well bore below sealin.	[Signed] Drilling Machine Operator)	12., 190	
Number of sacks of cement used in Well seal sacks			
How was cement grout placed? TUMPED			
	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this rep	ort is trice:	
	the best of my knowledge and belief.	7	
Was pump installed? Type HP Depth ft	Nome DLEMANS NETL DKI	UNG	
Was a drive shoe used? Yes YNo Plugs Size: location ft	(Person, firm or corporation)	pe or print	
Did any strata contain unusable water?	Address 2075 DIO VIDE - GREATO	!.~\!	
Type of Water? depth of strata	[Signed] Daniel College	Ser.	
Method of sealing strata off	_ (Water Well Contractor)	, 4	
Was well gravel packed? Yes \(\subseteq \text{No} \) Size of gravel: \(\text{P.E.A.} \).	Contractor's License No. 23. Date.	, 19.0	
Our Jule 29 ft to 143 ft.			