NC

RECEIVED
JUN 23 1966
STATE ENGINEER
SALEM, OREGON

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

JOSe 2115

State Well No. 38/5w-33A

State Permit No. .....

(1) OWNER:
Name Oswald M Stautz
Address Box 43
Williams Oregon

(2) LOCATION OF WELL:
County Josephine Driller's well number
NE ¼ NE ¼ Section 33 T. 38S R. 5W W.M.
Bearing and distance from section or subdivision corner

TL 102

(3) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from 0 ft. to 64 ft. Gage 1/4
..." Diam. from ... ft. to ... ft. Gage ...
..." Diam. from ... ft. to ... ft. Gage ...

(7) PERFORATIONS: Perforated? ☐ Yes ☑ No
Type of perforator used
Size of perforations in. by in.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.

(8) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name ...
Type ... Model No. ...
Diam. ... Slot size ... Set from ... ft. to ... ft.
Diam. ... Slot size ... Set from ... ft. to ... ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Cement Grout
Depth of seal 38 ft. Was a packer used? No
Diameter of well bore to bottom of seal 9 5/8 in.
Were any loose strata cemented off? ☐ Yes ☑ No Depth ...
Was a drive shoe used? ☑ Yes ☐ No
Was well gravel packed? ☐ Yes ☑ No Size of gravel: ...
Gravel placed from ... ft. to ... ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 12 ft. below land surface Date 5-19-66
Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? Driller
Yield: 150 gal./min. with 50 ft. drawdown after 3 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 49 Was a chemical analysis made? ☐ Yes ☑ No

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 102 ft. Depth of completed well 102 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Decomposed Granite	0	56
Fractured Granite	56	64
Tombstone Granite with Fissures	64	102

Work started 5-18 1966 Completed 5-19 1966
Date well drilling machine moved off of well 5-19 1966

(13) PUMP:
Manufacturer's Name Fairbanks Morse
Type: Submersible Turbine H.P. 3

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME N F Paquin Drilling Co. (Person, firm or corporation) (Type or print)
Address 2820 So. River Rd. Grants Pass
Drilling Machine Operator's License No. 475
[Signed] N F Paquin (Water Well Contractor)
Contractor's License No. 275 Date June 10, 1966

(USE ADDITIONAL SHEETS IF NECESSARY)