NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED

WATER WELL REPORT DEC2 1974

State Well No. 385 5W-34 aa

STATE OF OREGON

(Please type or print) STATE ENGINEER
(Do not write above this lifeALEM, OREGON State Permit No.

·		
(1) OWNER:	(10) LOCATION OF WELL:	
1211	County Josephine Driller's well number	
Address Williams Hwy Ovegon	N. E 14 NE 14 Section 34 T. 385	
Williams Oregon	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well Deepening 🗆 Reconditioning 🗀 Abandon 🗋	<u> </u>	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 50 ft.	
Rotary Driven Domestic MIndustrial Municipal D	Static level /2 ft. below land s	urface. Date //-/4-74
Cable B Jetted	Artesian pressure lbs. per square	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6 "	
6 " Diam, from D ft. to 94 ft. Gage 1025	Depth drilled 100 ft. Depth of completed well 100 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum	n and aquifer penetrated,
PERFORATIONS: Perforated? W Yes   No.	with at least one entry for each change of format position of Static Water Level and indicate prince	
	MATERIAL	From To SWL
Type of perforator used Torry	· · · · · · · · · · · · · · · · · · ·	
Size of perforations /4 in. by 4 in.	Consomerate - Boulders	95 100 12
36 perforations from 88 ft. to 93 ft.	Brue Clay - Boulders	10012
perforations fromft. toft.		
perforations fromft. toft.	,	
(7) SCREENS: Well screen installed?   Yes  No		
Manufacturer's Name		
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam, Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes 🕱 No If yes, by whom?		
Wald: gal./min. with ft. drawdown after hrs.		
" - " "		
" " " " "		
Bailer test /8 gal./min. with /O ft. drawdown after 2 hrs.		
g.p.m.  g.p.m.  Depth artesian flow encountered	Work started 16-30- 1974 Complete	ed 1/-14- 1974
perature of water Depth artesian now encountered		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	//-/4- 1974
Well seal-Material used CEMENT	Drilling Machine Operator's Certification: This well was constructed under my	
Well sealed from land surface toft.	Materials used and information reported	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	11-11
Diameter of well bore below seal	[Signed] M Golding Machine Operator)	Date 11-26, 19.74
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	351
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisd	
Was a drive shoe used? X Yes \( \subseteq \) No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water?   Yes No	Name Calemans Well DIT	(Tope or print)
Type of water? depth of strata	Address 2060 N.W. Vine C	arants Pass
Method of sealing strata off	David of Ol	
	[Signed] (Water Well Contr	actor)
Was well gravel packed?   Yes No Size of gravel:	200	11-01 1074
Gravel placed from ft. to ft.	Contractor's License No. 280 Date	/