NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310-within 30 days from the date of well completion.

## WATER WELL REPORT RECEIVED

STATE OF OREGON

OCT 9 1973 state Well No. 35 5 5 W- 0

(Please type or print)

STATE ENGINEER Permit No. (Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Ben Mullinex	County Josephine Driller's well number 108
Address 411 Inena Old.	14 14 Section 30 T. 355 R. 5 W. W.M.
(2) TYPE OF WORK (1. 1)	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 48'
Rotary Driven Domestic Monday Industrial Municipal Domestic Not Industrial Municipal Domestic Not Industrial Domestic Domestic Not Industrial Domestic Domes	Static level 24 ft. below land surface. Date 9-30-7
Dug	And surface. Date / Sel
CACING INCOMALLED	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
6 "Diam. from	Depth drilled 80 ft. Depth of completed well 80 ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated?   Yes  No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	
Size of perforations in. by in.	
perforations from ft. to ft.	Vellow Clay Bouken to 10" 18 54 24
perforations from ft. to ft.	13 1/ 21 4
perforations from ft. to ft.	Black & White Chante 67 80 24
	Fractured
(7) SCREENS: Well screen installed?   Yes X No	
Manufacturer's Name	
Type Model No.	
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.	
Static State Set from the ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a sussess dark at 1.5 East =	
ins.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water $\mathcal{S} \delta^B$ Depth artesian flow encountered ft.	Work started 9-28 1973 Completed 9- 30 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 9-30 1973
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my
Diameter of well bore below seal in.	best knowledge and belief
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 788
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
f water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? MYes No Plugs Size: location ft.	Name C. P. Bushington Orillog
Did any strata contain unusable water? 🗌 Yes 🕱 No	(Person, firm or corpopation) (Type or print)
Type of water? depth of strata	Address 537 Salimino Dr. Grants Pass
Method of sealing strata off	[Simual K. O. Bearlantes
Was well gravel packed? [] Yes [Y] No Size of gravel:	[Signed]
Gravel placed fromft. toft.	Contractor's License No. 552 Date 10-2 1973
	19/3