The original and first contraction of this report are to be SEP 7 - 1972 STATE OF OREGON

STATE OF OREGON

STATE ENGINEER, SALEM, OFFICA THE ENGINEER ase type or print) within 30 days from the date SALEM. OR 30 (Do not write above this line)

5058 State Well No. 365 6 W - 176	bk
3990 State Permit No	

(1) OWNER:	(10) LOCATION OF WELL:			
Name CHARLES R. ALSPACH	County OSEPHALE Driller's well number			
Address 5905 LOUIER RIVER AD	SE 4SE 4 Section /7 T. 365 R. GW W.M.			
1 de la companya del companya de la companya del companya de la co	Bearing and distance from section or subdivision			******
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner		 -
New Well				
If abandonment, describe material and procedure in Item 12.	(11) THE OPERATOR OF THE OPERATOR OPERATOR OF THE OPERATOR OPERATOR OPERATOR O	. 11		
	(11) WATER LEVEL: Completed we	.m. Aust	^т а :	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	335	0	ft.
Rotary Driven Domestic Mindustrial Municipal Domestic Mindustrial Municipal D	Static level / ft. below land s	arface. D	Date 6	8-12
Dug	Artesian pressure lbs. per square	e inch. D	Date	
CASING INSTALLED: Threaded Welded	(40) ************************************			
CASING INSTALLED: Threaded Welded Work Good True Good Tr	(12) WELL LOG: Diameter of well below casing			
"Diam. from ft. to ft. Gage ft. Gage	Depth drilled 6/ ft. Depth of completed well 6/ ft.			ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a			
Dillin Itom	and show thickness and nature of each stratum with at least one entry for each change of format			
PERFORATIONS: Perforated? Yes [] No.	position of Static Water Level and indicate princ	ipal wate	e r- bearin	ng strata.
Type of perforator used TOPCH	MATERIAL	From	То	swL
Size of perforations // in. by 4 in.	DEVOUNDED GAMNITE	0	5	
18 perforations from 54 ft. to 60 ft.	CREY GRAVEL -12" BOUDER	5 4	50	10
perforations fromft. toft.	DROWPOSED GRANITE	7)	61	10
perforations from ft. to ft.			- (
(7) SCREENS: Well screen installed? Yes X No				
Manufacturer's Name				
TypeModel No.				
Diam. Slot size Set from ft.		-		
Diam. Slot size Set from ft. to ft.				<u> </u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes 🕱 No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
, , , , , , , , , , , , , , , , , , ,				
	Management of the Control of the Con	<u> </u>		
Bailer test 30 gal./min. with 3 ft. drawdown after 2 hrs.				
Artesian flow g.p.m.			a	1077
mperature of water Depth artesian flow encountered ft.	Work started 6 5 1972 Complete	0 6	7	1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6-9	<u>/</u>	19/2
Well seal-Material used CEMENT	Drilling Machine Operator's Certification:			
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	above a	super re truc	vision.
Diameter of well bore to bottom of seal in.	best knowledge and wellef.	1	3-2- 	ריידע
Diameter of well bore below seal in.	[Signed] faces Usurum	DateO_	50	, 19.72
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	762	2	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		<i></i>	
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdi	ction an	d this	report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.			
Was a drive shoe used? X Yes \(\sum \) No Plugs Size: location ft.	Name COLEMANS WELL DULLING			
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) Address ZCCO UNE GRAVI	~ /\d	pe or pri	006
Type of water? depth of strata	Address LLCC3VIVE CHATTOUT		7.7,.(JAN.
Method of sealing strata off	[Signed]	6	A	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	actor)		
Gravel placed from ft. to ft.	Contractor's License No 380 Date	2 <u>- 3</u> 2	2	, 19. 7.2