NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.



STATE OF OREGONJUN 1 1 1974

(Please type or print TATE ENGINEER State Permit No. (Do not write above this SMEEM, OREGON

	State	Well	No.	707	1.5	W	****	Ø	Ð	K
,					ķ					

(1) OWNER:	(10) LOCATION OF WELL:						
Name Town Hies							
Address 2202 N.W. Highland							
Grants Pass, Oregon	NW 1/4 NE 1/4 Section 6 T. 365R. 5W W.M.						
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner						
New Well 💢 Deepening 🗍 Reconditioning 🗍 Abandon 📙							
If abandonment, describe material and procedure in Item 12.	(11) ****						
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.						
Rotary Driven	Depth at which water was first found 102 ft.						
Cable	11. below land surface. Date 4-26-7						
Integration Test wen Other	Artesian pressure lbs. per square inch. Date						
CASING INSTALLED: Threaded □ Welded 🔀	(19) YURY I TOG						
6 " Diam. from O ft. to 92 ft. Gage 025	(12) WELL LOG: Diameter of well below casing6"						
"Diam. fromft. to	Depth drilled 104 ft. Depth of completed well 104 ft.						
ft. Gage	Formation: Describe color, texture, grain size and structure of materials;						
PERFORATIONS: Perforated? V. Vog. C. N.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in						
Terrorated: A les No.	position of Static Water Level and indicate principal water-bearing strata.						
Type of perforator used	MATERIAL From To SWL						
Size of perforations // in. by // in.	Decomposed Granite + Clay 0 25 -						
39 perforations from 8.5 ft. to 9/ ft.	Decomposed Granito 25 104 6						
perforations fromft. toft.							
perforations from							
(7) SCREENS: Well screen installed? West No							
Manufacturer's Name							
TypeModel No							
Diam. Slot size Set from ft. to ft.							
Diam. Slot size Set from ft. to ft.							
(8) WELL TESTS: Drawdown is amount water level is							
lowered below static level							
Was a pump test made? Yes No If yes, by whom?							
Yield: gal/min. with ft. drawdown after hrs.							
" " " The second of the second							
The second of th							
Bailer test 40 gal./min. with 96 ft. drawdown after 2 hrs.							
Artesian flow g.p.m.							
perature of water Depth artesian flow encountered ft.	Work started 4-24 19 74/ Completed 4-24 19 74/						
(9) CONSTRUCTION:	Date well drilling machine mand of the state						
Well seal-Material used							
777-717-7 0	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.						
Diameter of well bore to bottom of sealin.							
Diameter of well bore below seal	best knowledge and belief.						
Number of sacks of cement used in well seal sacks	[Signed] MILLA H. Man (ISCO Date 5-28, 1974)						
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 850						
Brand name of bentonite							
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:						
of waterlbs./100 gals	This well was drilled under my jurisdiction and this report is						
Was a drive shoe used? Yes No Plugs Size: location ft.	the to the best of my knowledge and belief.						
Did any strata contain unusable water? Yes X No	Name (Person, firm or corporation) (Type or print)						
Type of water? depth of strata	Address 2060 N.W. VINE Grant - Pass						
Method of sealing strata off	0 10 00						
Was well gravel packed? ☐ Yes ⋈ No Size of gravel:	[Signed] Joseph Toleran						
	(Water Well Contractor)						
Gravel placed from ft. to ft.	Contractor's License No. 380 Date 5-28- , 1974						