The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date

Gravel placed from .

(Please type or priBTATE ENGINEER No.

or wen completion. (Do not write as	OVE THIS MEDALEM. OREGON		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Robert Taylor	County Josephine Driller's well number -28-		
Address 1241-Dowell Road	5-W 14 N-W14 Section 24 T. 36-SR. 6-West W.M.		
Grants Pass, Oregon-97526	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Tax 10t-#-5 - TAX-LOT- 2/02		
New Well X Deepening □ Reconditioning □ Abandon □	(PDV)		
If abandonment, describe material and procedure in Item 12.		11	,
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 9' ft.		
			ft.
Rotary □ Driven □ Domestic □ Industrial □ Municipal □	Static level 12 ft. below land s	ırface. Date	10-1-1
Oug Bored Irrigation Test Well Other X Trailer Court*	Artesian pressure lbs. per square	inch. Date	
CASING INSTALLED: Threaded □ Welded X	(12) WELL LOG: Diameter of well b	ology souther	6"
6 " Diam. from 0 ft. to 78 9" ft. Gage .250	Depth drilled 80 ft. Depth of comple	<u> </u>	
" Diam. from ft. Gage			
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum		
PERFORATIONS: Perforeted? D Veg 151 No.	with at least one entry for each change of format position of Static Water Level and indicate princ		
rentorated? [] les [] No.		npar water-oe	aring strata.
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Brown Granite Fill.	0 2	2
perforations fromft. toft.	Loose Medium To Large		
perforations from ft. to ft.	Loose Gravel & Sand.	2 24	-
perforations from ft. to ft.	Small Boulders & Medium	01 -	
7) SCREENS: Well screen installed? Ves X No	Firm Gravel & Sahd.	24 35	5
Manufacturer's Name	Tight Cemented Gravel & Sand With some clay.	75 50	,—
Type Model No.		35 78	5
Diam Slot size Set from ft. to ft.	Medium To Large Washed	78 80	12'
Diam ft. to ft,	Loose Gravel & Some Sand.	10 00	1 75
8) WELL TESTS: Drawdown is amount water level is lowered below static level			 -
Was a pump test made? ☐ Yes X☐ No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " " "			
n n n			
Sailer test 50 gal./min. with 45 ft. drawdown after 2 hrs.			
Artesian flow g.p.m.			
perature of water 54 Depth artesian flow encountered ft.	Work started 10-2-72 19 Complete	a 10-6-7	2 19
9) CONSTRUCTION:	Date well drilling machine moved off of well	10-7-72	19
Vell seal—Material usedCement	Drilling Machine Operator's Certification:		
Vell sealed from land surface toft.	This well was constructed under my	direct sup	ervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported- best knowledge and belief.	anove are r	rue to my
Diameter of well bore below sealin.	Signed les Sanakarbate 10-7 1972		
Jumber of sacks of cement used in well seal 12 sacks	(Drilling Machine Operator)		
Tumber of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No		
Brand name of bentonite	Water Well Contractor's Certification:		
Tumber of pounds of bentonite per 100 gallons			
f water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Vas a drive shoe used? X Yes No Plugs Size: location ft.	Name Les-Shanahan-Water-Well-Drilling-Co.		
Old any strata contain unusable water? X Yes No	(Person, firm or corporation) (Type or print)		
ype of water? Surface. depth of strata 9' to 18'	Address 868-N-E-"A"-St. Grants Pass, Oregon.		
Method of sealing strata off Cased & Cemented.	[Signed] Sa Mana Han		
Was well gravel packed? ☐ Yes 🔀 No Size of gravel:	(Water Well Contractor)		

Contractor's License No. 81-