NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## RECEIVED WATER WELL REPORT STATE OF OREGON MAR 13 1975 State Well No. 365 6W-24

(Please type or print) STATE ENGINEER

(Do not write above this lingALEM, OREGONState Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Fern Dixon	County Josephine Driller's well number
Address 1227 Redwood Ave	14 14 1414 Section 24 T. 365 R. 6W W.M.
Grants Pass, Ovenou	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	and distance from section of subdivision corner
New Well   Deepening □ Reconditioning □ Abandon □	, 100 Marie 16 - 15 - 15 - 15 - 15 - 15 - 15 - 15 -
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55 ft.
Rotary Driven Domestic M Industrial Municipal Domestic	Static level 29 ft. below land surface. Date /-24-75
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below casing
6 "Diam. from 0 ft. to 60 ft. Gage 025	Depth drilled 59 ft. Depth of completed well 59 ft.
"Diam from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Torch	MATERIAL From To SWL
Size of perforations /4 in. by // in.	Topsoil- 02 -
36 perforations from 52 ft. to 58 ft.	Decomposed Granite
perforations from ft. to ft.	27d Grave 1 4-1 2 59 29
perforations fromft. toft.	
(7) SCREENS: Well screen installed?   Yes No	
Manufacturer's Name	
Type Model No	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes 🕱 No If yes, by whom?	
d: gal./min. with ftdrawdown after hrs.	
" " " "	
n n	
Bailer test 20 gal./min. with /9 ft. drawdown after 2 hrs.	
sian flow g.p.m.  Temperature of water Depth artesian flow encounteredft.	
	Work started /- 2/- 1975 Completed /- 24 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well /-24 19 75
Well seal-Material used Coment	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Well sealed from land surface to	Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below sealin.  Number of sacks of cement used in well sealsacks	[Signed] (Orilling Machine Operator) Date 2-26-, 19.75
Number of sacks of cement used in well sealsacks  Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 939
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? K Yes 🗌 No Plugs Size: location ft.	
Did any strata contain unusable water?   Yes No	Name Coleman 5 Wells Drilling Company (Person, firm or corporation) (Type of print)
Type of water? depth of strata	Address 2060 N. W. Vinc. Grants Pass
Method of sealing strata off	[Signed] Sosel Page
Was well gravel packed? ☐ Yes X No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 380 Date 2726 1976