NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the 1.4 201

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 365-6w-26
State Permit No. 105EFMITE

(1) OWNER:	(10) LOCATION OF WELL:
Name COLLAGE HEIGHTS BAPTIST CHURCH Address 1832 DOWELL RD GRANTS PASS GRE	County Driller's well number
Address 1832 DON SLL RD GRANTS PASS OF	LE 14 NE 14 Section 26 T. 36 R. 6 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner . N.S
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	387 in to thell.
If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL Completed well
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
	Depth at which water was first found ft.
Cable	Static level 5 ft. below land surface. Date 3-73
Dug Bored Irrigation Test Well Other	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded Welded Threaded Welded Threaded Welded Threaded Threaded Threaded Threaded Welded Threaded Thr	(12) WELL LOG: Diameter of well below casing Depth drilled 37'/0" ft. Depth of completed well ft.
ft. to ft. Gage	
ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes Ino.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	to the second of
perforations from ft. to ft.	Hond Com Krown Hill house 1 16
perforations from ft. to ft.	The Dr. Mary John
perforations from ft. to ft.	on 11 Grandrich Some 1 1/2 28
(7) SCREENS: Well screen installed? Yes In No	
Manufacturer's Name	GRAVELIVIRD. 354 2314 15
Type Model No.	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes Ö No If yes, by whom?	
971-1-1	
* A * * * * * * * * * * * * * * * * * *	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
erature of water Depth artesian flow encounteredft.	Work started 19 Completed 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well
Well seal—Material used BENTONITE HATTIME	Drilling Machine Operator's Certification:
and the state of t	This well was constructed under my direct supervision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealfinfin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Cotton delicer Data 1003
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name LATHUR SCHNEIDER
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print) Address / Addr
Type of water? depth of strata	
Method of sealing strata off	[Signed]
Was well gravel packed? Yes No Size of gravel:	(water well Contractor)