NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT GEVE STATE OF OREGON MAR 8 1973 State Well No. 365 5 W-17

(Please type or pOTATE ENGINEER (Do not write above this MCLEM. OREGORIE Permit No. ...

(1) OWNER:	(10) LOCATION OF WELL:
Name Southern Chigon Vigwood	County Driller's well number
Address Box 269-Shorts Hosp, Ora	SE 1/4 5 W/4 Section / 7 T. 36 CR. 5 CW W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	D. L.C. #38
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 63 ft.
Rotary Driven Domestic Industrial Municipal	Static level /2 ft. below land surface. Date 3-2-7.3
Cable	
oug   Loren   Intgatton   1900 Hou   Others   La	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6
	Depth drilled 178 ft. Depth of completed well 167 ft.
ft. Gage	
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
DEDUCED A MYONG	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? Yes   No.	
Type of perforator used Mills Auto	MATERIAL From To SWL
Size of perforations 3/8 in. by 5 in.	Slack Clay 0 10
perforations from 63 ft. to 5 ft.	man H. Adila In 102
40 perforations from 90 ft. to 75 ft.	Mes. Show y Messey 10 63
200 perforations from 10 ft. to 134 ft.	mil shoul 63 65
(7) SCREENS: Well screen installed?   Yes De No	Wolfe Browing
Manufacturer's Name	Skriven Brown Clay & med. 65 90
Type Model No	Line of the state
Diam Slot size Set from ft. to ft.	Medi Gravel - Water Bearing 90 95
Diam. Slot size Set from ft. to ft.	1
The state of the s	Brown clas - Boulders & med. 95 110
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	2 Stravel
Was a pump test made? 🗆 Yes 🕩 No If yes, by whom?	med Annel - Water Blaring 110 135
yald: gal./min. with ft. drawdown after hrs.	0 10 10 10 10 10 10 10 10 10 10 10 10 10
" "	Boulders-Medi Graves 135 167
<u>"</u> " "	medi Around 167 178
test 05 gal./min. with/19 ft. drawdown after 2 hrs.	What to Rousing
Artesian flow g.p.m.	Wester seems
perature of water Depth artesian flow encountered ft.	Work started 2 - 26 1973 Completed 2 - 28 1973
14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Date well drilling machine moved off of well 2-3 8 19 23
(9) CONSTRUCTION:	
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief
Diameter of well bore below seal in.	[Signed] / Land Date 3-5, 19.73
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief
Did any strata contain unusable water?   Yes 1470	(Person, firm on corposition) (Type or print)
Type of water? depth of strata	Address 30 N.E. Elive G. Grant June
	Slower MENI.
Method of sealing strata off	[Signed (Water Well Contractor)
Was well gravel packed? ☐ Yes No Size of gravel:	1/4- 3-5 20
Gravel placed from ft. to ft.	Contractor's License No. Date