STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by OPS 537 765 & OAR 690-205-0210)

JOSE 59718

WELL I.D. LABEL# L
120672

START CARD # 1029465

ORIGINAL LOG #

(as required by ORS 537.765 & OAR 690-205-0210)	2/1/2016	ORIGINAL LOG#	1023 100	
(1) LAND OWNER Owner Well I.D.			,	
First Name RANDAL Last Name BROWN	(9) LOC	ATION OF WELL (legal de	escription)	
Company		EPHINE Twp 40.00 S N/S		W E/W WM
Address 5504 SE 136TH AVE		NW 1/4 of the NE		
City PORTLAND State OR Zip 97236 (2) TYPE OF WORK New Well Deepening Conversion				
	Lat	mber o " or 42.10735000		DMS or DD
Alteration (complete 2a & 10) Abandonment(complete 2a) PRE-ALTERATION	Long	°' or123.607840	00	DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd	•	Street address of well Nea	rest address	
Casing:	5047 TAKI	LMA RD CAVE JUNCTION, OR 9	97523	
Material From To Amt sacks/lbs				
Seal: (3) DRILL METHOD	(10) STA	TIC WATER LEVEL		
X Rotary Air Rotary Mud Cable Auger Cable Mud	(10) 5111	Date	SWL(psi) +	SWL(ft)
Reverse Rotary Other		g Well / Pre-Alteration		
	Comple	ted Well 1/21/2016		32
(4) PROPOSED USE Domestic Irrigation Community		Flowing Artesian?		
Industrial/ Commericial Livestock Dewatering			ter was first found _	
Thermal Injection Other	SWL Date	e From To Est	Flow SWL(psi)	+ SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard (Attac	ch copy) 1/21/2016	5 136 157	35	32
Depth of Completed Well 160.00 ft.				
BORE HOLE SEAL	sacks/			
Dia From To Material From To Amt	lbs			
10 0 20 Bentonite Chips 0 20 16 6 20 160 Calculated 9.13	S			
0 20 100	(14) 11/01	1100		
Calculated	(11) WEL	L LOG Ground Elevation	1 1444.00	
How was seal placed: Method A B C D E		Material	From	То
X Other DRY POURED		LAY COBBLES & MIXED GRAV		63
Backfill placed from ft. to ft. Material		N CLAY W/CRS SAND MIXED G	RAVI 63 81	96
Filter pack from ft. to ft. Material Size		MIX GRAVL & CRS SAND LAY MED GRAVL FINE SAND	96	118
Explosives used: Yes Type Amount	TAN CLAY		118	127
(5a) ABANDONMENT USING UNHYDRATED BENTONITE		LAY MIXED GRAVEL & CRS SA	AND 127	136
Proposed Amount Actual Amount	DK BRWN	CLAY MIXED GRAVL & CRS SA	AND 136	160
(6) CASING/LINER				
Casing Liner Dia + From To Gauge Stl Plstc Wld	Thrd			
● 6 × 1.5 118.5 .250 ● X				
	H			
	H II			
Shoe Inside Outside Other Location of shoe(s) 118.5				
Temp casing Yes Dia From To				
(7) PERFORATIONS/SCREENS				
Perforations Method				
Screens Type Material	Date Start	ed <u>1/21/2016</u> Comp	oleted 1/21/2016	
	Tele/) Water Well Constructor Certific		
Screen Liner Dia From To width length slots pip		at the work I performed on the con		ng, alteration, or
	abandonme	nt of this well is in compliance	e with Oregon wa	ter supply well
		standards. Materials used and inf	formation reported a	above are true to
		ny knowledge and belief.		
	License Nu	mber Da	te	
(8) WELL TESTS: Minimum testing time is 1 hour	Signed			
Pump Bailer • Air Flowing Artesi	an			
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	¬ l` ′	ater Well Constructor Certificati		
35 118 1		ponsibility for the construction, de		
		med on this well during the constructioning this time is in compliance		
Temperature 54 °F Lab analysis Yes By		standards. This report is true to the		
	pm License Nu	_	te 2/1/2016	
From To Description Amount Un	its		2/1/2010	
		EVIN D GILL (E-filed)		
	Contact Info	o (optional) Clouser Drilling Inc.		