STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) **JOSE 59727**

WELL I.D. LABEL# L 12
START CARD # 10
ORIGINAL LOG #

		ragerori	
L	121209		
	1029881		

(as required by ORS 537.765 & OAR 690-205-0210) 3/1	1/2016 ORIGINAL LOG #
(1) LAND OWNER Owner Well I.D.	
First Name C/O BLAKE & AMANDA Last Name METZLER	(9) LOCATION OF WELL (legal description)
Company LOFLAND LLC	County Josephine Twp 38.00 S N/S Range 5.00 W E/W WM
Address 560- A NE "F" ST. #641	Sec 23 SE 1/4 of the NE 1/4 Tax Lot 121
City GRANTS PASS State OR Zip 97526	
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot DMS or DD
Alteration (complete 2a & 10) Abandonment(complete 5	α, Ι
(2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd	Long One of the long DMS or DD Street address of well Nearest address DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd Casing:	483 LOFLAND LANE WILLIAMS, OR 97544
Material From To Amt sacks/lbs	1400 EOI E/IND E/INE WIEEE/IMB, OK 7/344
Seal:	
(3) DRILL METHOD	(10) STATIC WATER LEVEL
X Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) + SWL(ft)
Reverse Rotary Other	Existing Well / Pre-Alteration
	Completed Well 3/9/2016 12
(4) PROPOSED USE	Flowing Artesian? Dry Hole?
Industrial/Commericial Livestock Dewatering	WATER BEARING ZONES Depth water was first found 76.00
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard (Attach co	Py) 3/9/2016 76 126 30 12
Depth of Completed Well 140.00 ft.	377/2010 70 120 30 12
BORE HOLE SEAL sach	55/
Dia From To Material From To Amt 1b	
10 0 19 Bentonite Chips 0 19 12 S	
6 19 140 Calculated 8.67	
Calculated	(11) WELL LOG Ground Flevation
	Glound Elevation
How was seal placed: Method A B C D E Other DRY POURED	Material From To TAN BROWN CLAY TIGHT 0 19
Backfill placed from ft. to ft. Material	BROWN CLAY MIXED GRAVEL/COBBLES 19 34
	TAN CLAY COARSE SAND & MIX GRVL SILT 34 51
Filter pack from ft. to ft. Material Size	BROWN CLAY CRS SAND GRVL & BLDRS SILT 51 72
Explosives used: Yes Type Amount	BROWN DECOMPOSED GRANITE 72 123
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	GREY BROWN DECOMPOSED GRANITE 123 140
Proposed Amount Actual Amount	
(6) CASING/LINER	
Casing Liner Dia + From To Gauge Stl Plstc Wld Th	d
$lackbox{ } lackbox{ } lac$]
]
Shoe Inside Outside Other Location of shoe(s) 76	
Temp casing Yes From To	
(7) PERFORATIONS/SCREENS	
Perforations Method Saw Cut	
Screens Type Material	Date Started 3/9/2016 Completed 3/9/2016
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	
Screen Liner Dia From To width length slots pipe size Perf Liner 4 120 140 .188 4 60	I certify that the work I performed on the construction, deepening, alteration, or
1 C11 Line 7 120 140 .100 4 00	abandonment of this well is in compliance with Oregon water supply well
	construction standards. Materials used and information reported above are true to
	the best of my knowledge and belief.
	License Number Date
(8) WELL TESTS: Minimum testing time is 1 hour	· L
Pump Bailer • Air Flowing Artesian	Signed
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification
30 140 1	I accept responsibility for the construction, deepening, alteration, or abandonment
	work performed on this well during the construction dates reported above. All work
	performed during this time is in compliance with Oregon water supply well
Temperature 55 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge and belief.
· — — — — — — — — — — — — — — — — — — —	License Number 1835 Date 3/10/2016
Water quality concerns? Yes (describe below) TDS amount 270 ppm From To Description Amount Units	
	Signed KEVIN D GILL (E-filed)
	Contact Info (optional) Clouser Drilling Inc.