NOTICE TO WATER WELL CONTRACTOR The original and first copy	LL REPORTOV 1 9 1974		,	
of this report are to be filed with the	OREGONSTATE ENGINEERstate Well No.	395	18W.	-22
within 30 days from the date	SALEM, OREGON _{State Permit N}	0		
of well completion. (Do not write al	CAVE JUNCT		• -	
(1) OWNER:	(10) LOCATION OF WELL:			-
I show A Call D'T	County Joge Alin & Driller's well number			
Address 7/4 NW: A Gran 19 p/433, 09	* <u>14 14 Section 22 T. 39.5 R. 9417</u> W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner		·····
New Well IP Deepening [] Reconditioning [] Abandon []				
If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Driven	Depth at which water was first found 130 ft.			
Cable [] Jetted []	Static level 45 ft. below land surface. Date 14-1-14			
Dug 🛛 Bored 🗋 Irrigation 🗋 Test Well 🗌 Other 🗌	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded "Diam. fromft. toft. Gage	(12) WELL LOG: Diameter of well below casing			
" Diam. from	Formation: Describe color, texture, grain size and structure of materials;			
Diani, Honi II. Gage	and show thickness and nature of each stratum with at least one entry for each change of forma			•
PERFORATIONS: Perforated? [] Yes [] No.	position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Ged CAV	0	25	
ft. to ft.				
perforations from ft. to ft. to ft. to ft.	GREEN CLAY	25	40	
(7) SCREENS: Well screen installed? Yes Zi No	Red Clay gRAVE SM	40	45	
Manufacturer's Name	Blue Clay	45	107	
Type	For Alexander			
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	<u> [KAKI CIAYSTOWE BIAKK</u>	107	121	
(8) WELL TESTS: Drawdown is amount water level is	The state of the s			<u> </u>
Was a pump test made? I Yes [] No If yes, by whom?	PRACI CIAYSTONIE (MACK) HARD	121	155	
Yield: 39 gal./min. with 66 ft. drawdown after hrs.				
" " "	STRATA	130	140	38
, , , , , , , , , , , , , , , , , , ,	· · · · · · · · · · · · · · · · · · ·	ļ		
Bailer test gal./min. with ft. drawdown after hrs.		ļ		<u> </u>
		<u> </u>		······································
Artesian flow g.p.m. mperature of water 49 Bepth artesian flow encountered ft.	11.1 7.1			
mperature of water 71 Depth artesian flow encountered ft.	Work started //- 6 19 / Complete	ed //	-7	$\frac{19}{24}$
(9) CONSTRUCTION:	Date well drilling machine moved off of well		1-7	
Well seal-Material used <u>CEMENT</u>	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my			
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.			
Diameter of well bore below seal in.	[Signed] D.E. Hum	Date	1-10	., <u>19</u> 74
Number of sacks of cement used in well seal sacks	[Signed] . E. Munn Date 11-10, 1974 (Drilling Machine Operator) Drilling Machine Operator)			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		······	<u></u>
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is			
of water	true to the best of my knowledge and belief.			
Was a drive shoe used? I Yes I No Plugs	Name JA QUIN Drilling Co.			
Did any strata contain unusable water? 🗋 Yes 😰 No	(Person, firm or corporation)	0	pe or prin	1t)
Type of water? depth/of strata	Address 1940 Willow An Granty PASTO			
Method of sealing strata off	[Signed] C. I Pringtuist			
Was well gravel packed? Ves No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 5.46 Date	1.[15		., 19. 74 /-
(USE ADDITIONAL SI	HEETS IF NECESSARY)			*45656-119
· · · · ·				· ··]