The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 9, within 30 days from the date of well-completion.

Jose 10592

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JAN 19 1976 WATER RESOURCES DEPT. SALEM, OREGON

State Well No. 39/8-22

State Permit No.

(1) OWNER:
Name MR Theodor Kiwitt
Address 977 Caves Highway
Cave Junction Ore

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
2" Diam. from 0 ft. to 70 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Cutting Torch
Size of perforations 3/16 in. by 5 in.
35 perforations from 50 ft. to 70 ft.
perforations from 30 ft. to 50 ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 40 gal./min. with 40 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 56° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 20 FT ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:

(10) LOCATION OF WELL:
County Josephine Driller's well number
NW ¼ SW ¼ Section 22 T. 39 R. 8W W.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 45
Static level 12 ft. below land surface. Date Aug 31
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 70 ft. Depth of completed well 70
Formation: Describe color, texture, grain size and structure of material and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay gravel	0	35	
med gravel clay	35	45	
med gravel	45	70	

Work started Aug 29 1973 Completed Aug 31 1973
Date well drilling machine moved off of well Aug 31 1973

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] H Roy Cooper (Drilling Machine Operator) Date Sept 15 1973
Drilling Machine Operator's License No. 773

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name SOUTH STATE DRILLING CO. (Person, firm or corporation) (Type or print)
Address 825 Summit Loop, Grants Pass Oregon
[Signed] (Water Well Contractor)