

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310within 30 days from the date
of well completion.

RECEIVED

MAR 19 1979

WATER RESOURCES DEPT.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No.

State Permit No.

385/8W-26c

Jose
16614

(1) OWNER:

SALEM, OREGON

Name HASKELL SMITH
Address 366 PINE TREE WAY
SEASIDE, ORE

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

6" Diam. from 0 ft. to 20 ft. Gage 1.250
" Diam. from 0 ft. to 129 ft. Gage
4" Diam. from 0 ft. to 129 ft. Gage SCH. 40-PVC

PERFORATIONS:

Perforated? ☒ Yes ☒ NoType of perforator used SAWSize of perforations 3/8 in. by 3 in.
75 perforations from 115 ft. to 129 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ NoManufacturer's SAW
Type SAW Model No. SAW
Diam. Slot size SAW ft. to ft.
Diam. Slot size SAW Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static levelWas a SAW test made? ☒ Yes ☐ No If yes, by whom? DRILLERYield: 2 gal./min. with ft. drawdown after 1 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 50° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENTWell sealed from land surface to 20 ft.Diameter of well bore to bottom of seal 10 in.Diameter of well bore below seal 6 in.Number of sacks of cement used in well seal 7 sacksHow was cement grout placed? PUMPEDWas a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel: ft.

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County JOSEPHINE Driller's well number
SW 1/4 NW 1/4 Section 2 T. 38 R. 8W W.M.

Bearing and distance from section or subdivision corner

TAX LOT 2100

(11) WATER LEVEL: Completed well.

Depth at which water was first found 115 ft.Static level 4.2 ft. below land surface. Date 3/15/79

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"Depth drilled 140 ft. Depth of completed well 140 ft.Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
CLAY, BROWN	0	53	
CLAY, BROWN, GRAVEL, SMALL	53	72	
CLAY, BROWN	72	89	
CLAY, BROWN, GRAVEL, SMALL	89	101	
SHALE BEDROCK, GREEN, FIRM	101	140	42'
AQUIFER	115	117	2 gpm

Work started 3/15 1979 Completed 3/15 1979Date well drilling machine moved off of well 3/15 1979

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.[Signed] D.L. Orust Date 3/15, 1979
(Drilling Machine Operator)Drilling Machine Operator's License No. 850

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.Name Paquin Well Drilling Inc.
(Person, firm or corporation) (Type or print)Address 1840 Willow Lane Grants Pass, Ore.[Signed] W.F. Paquin
(Water Well Contractor)Contractor's License No. 275 Date 4-15, 1979