## NOTICE TO WATER WELL CONTRACTOR The original and first copy of pieres E V EVATER WELL REPORT are to be filed with

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 FEB 2 8 1979 (Please type or print) within 30 days from the date of well completio ATER RESOURCES DEPTot write above this line)

STATE OF OREGON

State Well No. 355/6w-10ad
State Permit No. G-8744

SALEM. OREGON	(10) TOCATION OF WELL.
1) OWNER:	(10) LOCATION OF WELL:  County Togenhine Driller's well number 6
Tame George W. Moris	County JOSEPHILIE
Address 8690 Monument Dr.	5E 1/4 NE 1/4 Section 10 T. 35g R. 6w W.M.
Grants Pass, Oregon	Bearing and distance from section or subdivision corner
2) TYPE OF WORK (check):	Tax Lot 501
New Well Deepening Reconditioning Abandon	
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 108 ft.
Rotary Driven Domestic Industrial Municipal	Static level -0 - ft. below land surface. Date 3-1-79
Cable D Jetted	Artesian pressure — lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing6
6	Depth drilled 115 ft. Depth of completed well 115 ft.
" Diam. from	Formation: Describe color, texture, grain size and structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
	Dark Brown Gumbo top
Size of perforations in. by in.  perforations fromft. toft.	soil & Boulders 0 6
perforations fromft. toft.	
perforations fromft. toft.	Boulders medium to large
	with gravel & brown clay 6 74
(7) SCREENS: Well screen installed?   Yes You No	Hardpan containing boulders
Manufacturer's Name	1 7 1 7 7 7
Diam. Slot size Set from ft. to ft.	brown sand in color (4 145 0
Diam. Slot size Set from ft. to ft.	
in the level in	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?  Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" "	
n n n n	
Bailer test 50p gal./min. with 30 ft. drawdown after 2 hrs.	
Artesian flow -O- g.p.m.	
nperature of water 54 Depth artesian flow encounteredft.	Work started 26-12-78 19 Completed 3-1-79 19
(a) CONSTRUCTION:	Date well drilling machine moved off of well 3-1-79
(9) CONSTRUCTION:  Well seal—Material used Genment Slurry	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 26-2-7.919 (Drilling Machine Operator)
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No98
How was cement grout placed?	Diffing Machine Operators
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? A Yes   No Plugs Size: location ft.	NamicES SHANAHAN WATER WELL DRILLING. CO.
Did any strata contain unusable water?   Yes No	Q6Q NI TO HAll at Amenta Doga One
Type of water? depth of strata	
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? Yes No Size of gravel:	Contractor's License No81 Date26-2-79, 19
Gravel placed from ft. to ft.	Contractor's Enterise 140.