NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report
are to be filed withing the water resources default. WATER WELL REPO
WATER RESOURCES DEFAULT. WELL REPO WATER WELL REPORT

SALEM, OREGON 97310 within 30 days from the da NOV 14 1977 of well completion.

(Please type or print)

(Do not write above this line)



248/2M-2/18/8

State	Well No	·. 🔿	Oplon Tin	(
State	Permit	No.	Ahret-Transcount Minkessanson et al management and a serial management and a s	**

WATER RESOURCES DEPT.					
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:	#1			
Name Spalding & Son2345 SE "N" Street	County Josephine Driller's well no				
Address Grants Pass, OR	NE 1/4 NE 1/4 Section 21 T. 36s			W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner			
New Well KX Deepening   Reconditioning   Abandon				<del></del>	
If abandonment, describe material and procedure in Item 12.	(11) WADED LEVEL Complete				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w				
Rotary Driven Domestic Didustrial Winicipal D	Depth at which water was first found	40_	10/	ft.	
Cable	Static level 50 ft. below land s			15///	
	Artesian pressure lbs. per squar	e inch. D	ate	· 	
(J) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing				
6 "Diam from 0 ft to 145 ft Gage 250	Depth drilled 160 ft. Depth of compl		160	ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	and struct	ure of ma	teriale	
Diani. Honi II. Gage	and show thickness and nature of each stratu with at least one entry for each change of forma	m and ag	uifer nene	atrated	
PERFORATIONS: Perforated?   Yes X No.	position of Static Water Level and indicate prin	cipal wate	r-bearing	strata.	
Type of perforator used	MATERIAL	From	То	swl	
Size of perforations in. by in.	Clay, brown & Boulders	0	29		
perforations from ft. to ft.	Clay, brown impervious	29	45		
perforations from ft. to ft.	Clay, brown w/boulders	45	140		
perforations from ft. to ft.	Rock, gray hard w/fractures	140	160	50	
(7) SCREENS: Well screen installed? ☐ Yes X₺ No					
Manufacturer's Name					
Type Model No					
Diam. Slot size Set from ft. to ft.  Diam. Slot size Set from ft. to ft.					
Statil State Set from It. to It.		<b></b>			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? ☐ Yes, ☐ No If yes, by whom?					
Yield: gal./min. with ft. drawdown after hrs.					
" " "					
n n n					
Air and a gal./min. with 100 ft. drawdown after 1 hrs.					
Artesian flow g.p.m.					
perature of water Depth artesian flow encountered ft.	Work started 19/14 19 77 Complete		10/15	1977	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10	0/15	1977	
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification:				
Well sealed from land surface to	This well was constructed under my	direct	supervi	sion.	
Diameter of well bore to bottom of seal10 in.	Materials used and information reported best knowledge and belief.	above ar	e true t	o my	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 11	<b>/10</b> , j	19.77	
Number of sacks of cement used in well sealsacks  How was cement grout placed? Grout pump and drop pipe	Drilling Machine Operator's License No. 695				
was cement grout paced; Grout pump and Grop pripe.	operator a process and its				
	Water Well Contractor's Certification:				
	This well was drilled under my jurisdi- true to the best of my knowledge and beli	ction and	this rep	ort is	
Vas a drive shoe used ※▼ Yes □ No Plugs Size: location ft.	Name McClanahan Well Drilling				
Did any strata contain unusable water?   YesXX No	(Person firm of corporation)  Address 141 ME Beacon Brive (	Type	or print)	ΩP	
Type of water? depth of strata	Address 141/11 Beddyn 111/10	L'anys	yass,		
Method of sealing strata off	[Signed]	4/1/2	, ,		
Was well gravel packed? Tyes XX No Size of gravel:	(Water Well Cornra				
Gravel placed fromft. toft.	Contractor's License No. 614 Date No.	vember	: 11	<sub>19.77</sub>	