NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the C C WATER WELL REPORT WATER RESOURCES DEPARTMENT,

SALEM, OREGON 97310 within 30 days from the date of well completion.

NOV 14 1977 (Please type or print)
(Do not write above this line)
R RESOURCES DEPT

50 20 State Well No. 305 | SW-2130

State Permit No.

WATER RESOURCES DEPT				
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL: #2			
Name Spalding & Son	County Josephine Driller's well number			
Address 2345 SE "N" Street	NE 14 NE 14 Section 21 T. 36s	-		****
Grants Pass, OR 97526	NE 1/2 NE 1/2 Section 2.1 T. JOS R. JW W.M. Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	Dearing and distance from section of subdivisi	on corne	<u>r</u>	<u></u> _1
New Well [XX Deepening ☐ Reconditioning ☐ Abandon ☐				·
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 60 ft.			
Rotary 📆 Driven 🗌 Domestic 🗌 Industrial 🔀 Municipal 🗍	, , , , , , , , , , , , , ,			
Dug				
CASING INSTALLED: Threaded Welded K 6 "Diam from 0 ft to 140 ft Gage 250	(12) WELL LOG: Diameter of well below casing 6 Depth drilled 160 ft. Depth of completed well 160 ft.			
" Diam. from	Formation: Describe color, texture, grain size	and struc	ture of i	materials:
	and show thickness and nature of each stratu with at least one entry for each change of forma	m and a tion. Ren	quifer pe	enetrated,
PERFORATIONS: Perforated?XK Yes No. Type of perforator used Mills Knife	position of Static Water Level and indicate prin			
Size of perforations 3/8 in. by 3 in.	MATERIAL CO. D. C.	From	To	SWL
105 perforations from 57 ft. to 120 ft.	Clay, brown & Boulders	25	25	
perforations fromft. toft.	Clay, brown heavy impervious Gravel, & Boulders	25 55	55 135	
perforations fromft. toft.	Rock, hard gray	135	160	20
(E) CODETENO				
(7) SCREENS: Well screen installed? ☐ Yes \X No				
Manufacturer's Name	-			<u> </u>
Diam. Slot size Set from ft. to ft.		-		
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes 🛣 No If yes, by whom?				
Weld: gal./min. with ft. drawdown after hrs.				
" " "	-			
" " " "				
Alr gal./min. with 100 ft. drawdown after 1 hrs.				
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started 10/18 19 77 Completed 10/20 19 77			
(9) CONSTRUCTION:	Date well drilling machine moved off of well		10/20	19 77
Well seal—Material used Cement grout	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above a	ire true	to my
Diameter of well bore below seal	[Signed] Meffert Cacref Date 11/9 , 1977			
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator) Drilling Machine Operator's License No. 695			
How was cement grout placed?Grout pump and drop pipe.	Diming Machine Operator's License No			***
	Water Well Contractor's Certification:		-,	
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name McClanahan Well Drilling			
Did any strata contain unusable water? Yes WNo	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 141 No Deacon Brive Francis Pass, OR			
Aethod of sealing strata off	[Signed MMCM] MMM			
Was well gravel packed? ☐ YesX⊠ No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. Date November 11 , 19 77			