NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

of well completion.

WATER WELL REPORT

WATER RESOURCES DEPARTMENT TO THE STATE OF OREGON SALEM, OREGON 973 (Please type or print) within 30 days from the date

State Well No. 3	SW-24da
State Permit No	

JAN 10 1978 (Do not write above this line)

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:			
Name (AL WADE (WATANKETEGONTNN)	County JOSEPHINE Driller's well number			
GRANTS PASS, OREGOIN	5E 1/8 SE 1/4 Section 24 T. 36 R. 5W W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner		·
New Well Deepening □ Reconditioning □ Abandon □	1/1/2 < 0.1 3 400			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	48		ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land s	surface. I	Date 1 2	2-16-77
Cable	Artesian pressure lbs. per squar			
CASING INSTALLED: "Diam. from ft. to ft. Gage 250 "Diam. from ft. to ft. Gage 7 Diam. from ft. Gage 7 Diam. ft. Gage 7 Diam	(12) WELL LOG: Diameter of well below casing			
Type of perforator used Mills KNIFE	MATERIAL	From	То	swL
Size of perforations 3/8 in. by 2 h in.	Clay Brown	0	14	
\$0 perforations from \$40 ft. to \$5 ft. perforations from \$10 ft. to \$10 ft.	Clay BROWN, Boulders	14	45	
60 perforations from 135 ft. to 160 ft.	CARGE			
(E) CORRELIC.	Consumble design	6.0		4
(1) SCILLINS: Well screen installed? Yes No Manufacturer's Name	GRAVET LARGE, SANDY	45	55	41.
Type Model No.	Clay Brown, GRAVET			
Diam. Slot size Set from ft. to ft.	LARGE	55	128	
Olam. Slot size Set from ft. to ft. (8) WELL TESTS: Drawdown is amount water level is	Clay BROWN	128	135	
Was a pump test made? Ves \(\text{No If yes, by whom?} \) Yield: Q gal./min. with 7 ft. drawdown after hrs.	FRACTURED BASALT, Clay BROWN	135	159	41'
	BASALT BEDROCK	159	225	
		1		14 01
	HguifeR	47	<u>48</u> 140	Va clas
perature of water Depth artesian flow encountered	Work started 12-16 1977 Complet	10	-72	2 10 7 7
	Date well drilling machine moved off of well	1 4)_1:	2 10 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
(9) CONSTRUCTION: CEMENT		17		<u> </u>
well seal—waterial used	This well was constructed under my		super	rvision.
Well sealed from land surface toft.	Materials used and information reported			
Diameter of well bore to bottom of sealin. in. Diameter of well bore below sealin.	best knowledge and belief	Data 1	1-2	7, 1977
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		81	•
How was cement grout placed? PUMP GROUT	Drilling Machine Operator's License No.		0.19	
	Water Well Contractor's Certification:			
	This well was drilled under my jurisd true to the best of my knowledge and be		d this	report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	Name PAQUIN DRILLING			
Type of water? depth of strata	Address 1840 Willow LN. 2	,	pe or pri	iss, ORL
Method of sealing strata off	Of May			- Jane
	[Signed] (Water Well Cont	ractor)		
Was well gravel packed? Tes No Size of gravel:	Contractor's License No. 22 Date	4 8	27	10 77
Gravel placed from ft. to ft.	Contractor's License No Date		id	, 13.₹∤