NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

3946

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

-		10 , 20 1
State Well	No.355	5W-30cd

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:			
Name Linda Intlekoser	County Josephine Driller's well nu	mber	214	
Address 445 Colonial Drive		R. 5w		W.M.
Grants Pass, OR 97526	Bearing and distance from section or subdivision			
(2) TYPE OF WORK (check):	Tax Lot 1000	, corne		
New Well ☒X Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w			
(3) TYPE OF WELL: (4) PROPOSED USE (check):				
Rotary XX Driven []	Deput at which water was mist tound	50		<u>ft.</u>
Cable				
Dug Bored Irrigation Test Well Other	Artesian pressure 14 lbs. per squar	e inch.	Date 5/	/15/78
CASING INSTALLED: Threaded Welded KK	(12) WELL LOG: Diameter of well h	_	. 6	 5
6 "Diam. from 0 ft. to 118 ft. Gage)			
	Depth drilled 120 ft. Depth of comple			20 ft.
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum	ind struc	cture of r	materials;
A	with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes XX No.	position of Static Water Level and indicate prin	cipal wa	ter-bearii	ng strata.
pe of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Clay, & Soil black/brown	0	10	
perforations from ft. to	tt. Boulders, small & Gravel,			
perforations from ft. to	• • • • • • • • • • • • • • • • • • • •	10	20	
perforations from ft. to		W		
(7) SCREENS: Well screen installed? ☐ Yes ★★ No	& Gravel, med	20	35	
	Clay, red/brown impervious	35	42	
Manufacturer's Name	pourcers, med a graver, med.			
Type	The Oray Breeze	42	60	
Diam. Slot size Set from ft. to Diam. Slot size Set from ft. to	TYGTGETS WEGINER OF GITAGET		400	
Diant. Slot Size Set Holl It. W		60	100	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Granite, black/white hard	400	400	
	Artesian Zone	100	120	
Was a pump test made? Yes No If yes, by whom?		<u> </u>		
	rs.			
" "				
- N	"			
Exists test 25 gal./min. with 50 ft. drawdown after 1 h	rs.			
Artesian flow 5 g.p.m.				
perature of water Depth artesian flow encountered	ft. Work started 5/14 1978 Complete	eđ	5/27	19 78
(A) CONCERNICATION	Date well drilling machine moved off of well		5/27	19 78
(9) CONSTRUCTION:	D. W. W. Alice Occasion Continue			
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification: This well was constructed under my	direct	CHEAN	
Well sealed from land surface to	Materials used and information reported	above	are true	to my
Diameter of well bore to bottom of seal	best knowledge and belief	E-right	612	***
Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 4 yards.		Date	0/3	., 19/8
	Drilling Machine Operator's License No.	12	34	
How was cement grout placed? Poured in annular area.				
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdi	ction a	nd this r	eport is
Was a drive shoe used? ▼XYes □ No Plugs Size: location	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes TYNo	Name McClanahan Well Drilling (Person, firm or corporation)	,	ype or pri	nt)
Type of water? depth of strata			Pass,	
	de il n	10 C	//_	0
Method of sealing strata off	- [Signed]	LV	and	nan
Was well gravel packed? Yes No Size of gravel:	—	-	2	70
Gravel placed from ft to ft	Contractor's License No. 444 Date	June	J	10 78