NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.



STATE OF OREGON State Well No. (Please type or print)

(Do not write above this line) JUL 26 1978 State Permit No.

	LANGER CONDER BEDT		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Luther Barker	County Josephine Driller's well number 462-2		
Address 1530 Jenkins	NE ¼ NW ¼ Section 20 T. 35	в. б	W.M.
Grants Pass, OR 97526	Bearing and distance from section or subdivisi		********
(2) TYPE OF WORK (check):	Tax Lot 1300		
New Well □X Deepening □ Reconditioning □ Abandon □			· · · · · · · · · · · · · · · · · · ·
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	الم	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Donth of which waste		
Rotary XK Driven Domestic K Industrial Municipal Domestic		75	ft.
Dug	Autorian		1/15/78
CASING INSTALLED: Threaded C Wolded Y	Artesian pressure lbs. per square inch. Date		
	(12) WELL LOG: Diameter of well below casing		
6 " Diam. from 0 ft. to 75 ft. Gage •250	Depth drilled 100 ft. Depth of completed well 100 ft.		
"Diam from ft. to ft. Gage	Formation: Describe color, texture, grain size a		
"Diam. fromft. toft. Gage	and show thickness and nature of each stratu	m and acuifor	n nonotuated
PERFORATIONS: Perforated? Yes XX No.	with at least one entry for each change of format position of Static Water Level and indicate prin	tion Report on	ah ahamaa in
Type of perforator used	MATERIAL		
Size of perforationsin. byin.		From To	SWL
perforations fromft. toft.	Clay, brown & Gravel, sm/med		
perforations from ft. to ft.	& Boulders, small Clay, brown impervious	0 1	
perforations from ft. to ft.	Clay, blue impervious	15 25 25 35	
(7) CODERAG	Clay, blue/grey & Boulders,	25 3	2
(7) SCREENS: Well screen installed? ☐ Yes 💥 No	sm/med & Gravel, med	35 60	
Manufacturer's Name	Granite, black/white	33 00	'
Type Model No	fractured water bearing	60 100) 40
Diam. Slot size Set from ft. to ft.			- 10
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes xx No If yes, by whom?			
T-1.			
nrs.			
"".			
Äir 50		 -	
test 50 gal./min. with 80 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
Inperature of water Depth artesian flow encountered ft.	Work started 7/14 1978 Completed	7/15	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/15	
Well seal—Material used Cement Grout			19 -
Well sealed from land surface to 22	Drilling Machine Operator's Certification: This well was constructed under my	dinant a	
Diameter of well bore to bottom of seal 10 in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore below seal 6 in.	pest knowledge and belief.		
Number of sacks of cement used in well sealsacks	[Signed] Drilling Machine Operator) Date 7/18, 1978		
How was cement grout placed?	Drilling Machine Operator's License No. 1234		
Grout pump and drop pipe.			
and the second s	Water Well Contractor's Certification:		
and the state of t	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? XXYes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief. Name McClanahan Well Drilling		
Did any strata contain unusable water? Yes XXNo	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 141 NE, Beacon Drive Grants, Pass, OR		
Method of sealing strata off	Chara of Ma	1// //	
Was well gravel packed? ☐ YesxX No Size of gravel:	[Signed] (Water Well Contrac	RULKA	N/
Gravel placed from ft. to ft.			3 72
TV.	Contractor's License No. 422 Date	oury 10	, 19