NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT, JUL S 1 1978TATE OF OREGON SALEM, OREGON 97310
within 30 days from the date ATER RESOURCES DEPI.
of well completion.

CALFM COFFON.

2058	State Well N	. 355/	6W-3AL
8367			
	State Permit	No	-/A?

SALEM. 1. 4 ON	the state of the s	1,0,	
(1) OWNER:	(10) LOCATION OF WELL:		
Name Virgib Witcher	County peopline Driller's well number		
Address 410 Three Pines	NU 14 ME 14 Section 0 3 T 35 SR. C	<u> </u>	W.M.
GRAWTS PASS	Bearing and distance from section or subdivision co	rner	
(2) TYPE OF WORK (check):	TAXNOT 503		-
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	82	ft.
Rotary Driven Domestic Industrial Municipal	Static level /5 ft. below land surface	e. Date	-27-7
Cable	Artesian pressure lbs. per square inc	h. Date	
CASING INSTALLED: Threaded Welded D. Welded D. ft. to 7 ft. Gage 1025	(12) WELL LOG: Diameter of well below		,,
"Diam. from ft. to ft. Gage	Depth drilled /20 ft. Depth of completed	well / L	<u>e</u> ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and s and show thickness and nature of each stratum ar		
	with at least one entry for each change of formation.	Report each o	change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal	water-bearing	ig strata.
Type of perforator used	MATERIAL Fro	om To	SWL
Size of perforations in. by in.	Top soil	2/2	
perforations from ft. to ft.	1:1-00-0-17	1/2 15	
perforations from	Light GRAY GRANIT 2.	2/3	
perforations from ft. to ft.	apan aron't 15	- 90	15/
(7) SCREENS: Well screen installed? Yes No	The state of the s	1	
Manufacturer's Name	HARD GRAY ORAWIT 9	0 120	151
Type Model No	FRACTURES		
Diam Slot size Set from ft. to ft.			<u> </u>
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
Towered below static level			
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
ÄR """			
Bailer test & O gal./min. with 65 ft. drawdown after / hrs.			ļ
Artesian flow g.p.m.			<u> </u>
perature of water 54 Depth artesian flow encountered ft.	Work started 6 -26 1978 Completed	6-26	1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u>. 27</u>	1978
Well seal-Material used Cement GROUT	Drilling Machine Operator's Certification:	•	
Well sealed from land surface to	This well was constructed under my din Materials used and information reported abo		
Diameter of well bore to bottom of seal in.	best knowledge and belief.	AC OTC TIN	III
Diameter of well bore below seal	[Signed]	7-22	<u>, 19</u> 78
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	460	
How was cement grout placed? LAROUI PUNTO	Drilling Machine Operator's License No.		
	Water Well Contractor's Certification:		
· · · · · · · · · · · · · · · · · · ·	This well was drilled under my jurisdictio	n and this	report is
Was a drive chan yould Elvan C No Blura Circ. leastion &	true to the best/of my knowledge and belief.	A) 11	//
Was a drive shoe used? E Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	Name (Person, firm or corporation)	(Type or pri	int)
	Address 570 MONUMENT	DR	
Type of water? depth of strata		11/ 0	-
Method of sealing strata off	[Signed]		\sim
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor		-
Gravel placed from ft. to ft.	Contractor's License No. 14 Date Date	-22_	, 19/.