NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report , are to be filed with the

WATER WELL RECORD VED

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

Gravel placed from ft. to ft.

-STATE OF OREGONEP

State	Well	No.	395	-/8	a	-5	46	/ と

of well completion. (Do not write all	WILL OF CO.					
(1) OWNED.	(10) LOCATION OF WELL:	7.5				
(1) OWNER:	County Josephine Driller's well nur	mber 3 4/29				
Name MR. CUFFORD FLINT Address 40 GREEN VALLEY INVESTMENT	SW 14 NW14 Section 34 T. 395					
CAILE JUNCTION 925-23	Bearing and distance from section or subdivisio					
(2) TYPE OF WORK (check):		on W14 cor				
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		PC 34				
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.				
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	 90 . ft.				
Rotary N Driven Domestic N Industrial Municipal Domestic N Industrial	Static level 30 ft. below land st	urface. Date 8 /9				
Cable ' Jetted Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date					
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing				
6 " Diam. from Q ft. to 133 ft. Gage 250	Depth drilled /33 ft. Depth of completed well /33 ft.					
" Diam. from	Formation: Describe color, texture, grain size a					
Diam. from it. to it. Gage	and show thickness and nature of each stratur with at least one entry for each change of format					
PERFORATIONS: Perforated? 🖫 Yes 🗆 No.	position of Static Water Level and indicate prin	cipal water-bearing strata.				
Type of perforator used Cuting ToreH	MATERIAL	From To SWL				
Size of perforations 3/16 in. by 60 in.						
60 perforations from 113 ft. to 133 ft.	CLAY	0 30				
perforations from ft. to ft.	CLAY MED GRAVEL	30 100				
perforations from ft. to ft.	CLAY & MED. GRAVEL	30 700				
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	CAY	100 125				
Manufacturer's Name						
Type Model No	LARGE YMED. GRAVEL	125 133 30				
Diam. Slot size Set from ft. to ft.						
Diam. Slot size Set from ft. to ft.						
(8) WELL TESTS: Drawdown is amount water level is lowered below static level						
Was a pump test made? ☐ Yes ☒ No If yes, by whom?						
Weld: gal./min. with ft. drawdown after hrs.						
" " " "						
,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,						
Bailer test 50 + gal./min. with 0 ft. drawdown after 1 hrs.						
Artesian flow g.p.m.						
hperature of water Depth artesian flow encountered ft.	Work started 8/8 1978 Complete	ed 8/9 1978				
	Date well drilling machine moved off of well	8/9 1978				
(9) CONSTRUCTION:		7				
Well seal-Material used CEMENT CALOUT	This well was constructed under my					
Well sealed from land surface toft.	Materials used and information reported	above are true to my				
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	best knowledge and belief. [Signed] Dan Cloure	Data 8/22 1078				
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	. /				
How was cement grout placed?	Drilling Machine Operator's License No.	/257				
Poured	Water Well Contractor's Certification:					
- Andrew - A	This well was drilled under my jurisd	iction and this report is				
Was a drive shoe used? Ŋ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and bel	ief.				
Did any strata contain unusable water? Yes No	Name Ciouser Drillia (Person, firm or corporation)	(Type or print)				
Type of water? depth of strata	Address P.O. BW 435, SELA	1A 97538				
Method of sealing strata off	10.11					
	[Signed] (Water Well Contr	actor)				
Was well gravel packed? Yes No Size of gravel:	/	1				

Contractor's License No. 700