NOTICE TO WATER WELL CON PAFOC E VEALER WELL REPORT 2006

WATER RESOURCES DEPARTMENT OV 3 1978 STATE OF OREGON SALEM, OREGON 97310 (Please type or print) within 30 days from the parter RESOURCES DEPTrite above this line)

State Permit No.

SALEM. OREGON			
(1) OWNER:	(10) LOCATION OF WELL:		
Name Dick Westerburg	County Josephine Driller's well no	umber 539	
Address 505 NE 7th Street	SE 14 SE 14 Section 15 T. 38	R. 5w	W.M.
Grants Pass, oR 97526	Bearing and distance from section or subdivisi	on corner	,
(2) TYPE OF WORK (check):	Tax Lot 801		
New Well ☒χ Deepening ☐ Reconditioning ☐ Abandon ☐			· · · · · · · · · · · · · · · · · · ·
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	80	ft.
Rotary XX Driven Domestic XX Industrial Municipal	Static level 35 ft. below land a		
Cable	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing 6		
6 "Diam from 0 ft to 84 ft Gage .250	Depth drilled 200 ft. Depth of compl	eted well 2	00 ft.
" Diam from	Formation: Describe color, texture, grain size		
" Diam, from ft. to ft. Gage	and show thickness and nature of each stratu with at least one entry for each change of forma		
PERFORATIONS: Perforated?   Yes XX No.	position of Static Water Level and indicate prin		
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Clay, brown & Boulders	0 1	4
perforations from ft. to ft.	Clay, brown hard impervious	14 2	5
perforations from ft. to ft.	Clay, brown & Boulders	25 7	0
perforations from	Granite, decomposed med.hard	70 8	0
(7) SCREENS: Well screen installed?   Yes XX No	Granite, brown hard	ļ	
	water bearing	80 14	0
Manufacturer's NameModel No	Granite, brown/white,	140 20	0 25
Diam. Slot size Set from ft. to ft.	Wlack/white water bearing	140 20	0 35
Diam. Slot size Set from ft. to ft.		<del>                                     </del>	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made?   Yes   No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" "		ļ	
" " "		ļ	
Air sest 50 gal./min. with 160 ft. drawdown after 1 hrs.		<del>  </del>	
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 10/26 19 78 Complet	10	/27 1978
perature of water Depth aresian flow electricited			/27 <sub>19</sub> 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well		1910
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	above are	pervision. true to my
Diameter of well bore to bottom of seal 10 in.	best knowledge and belief.	,	
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date 10/3	1, 1978
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 1167		
How was cement grout placed?  Grout poured in annular space.			
	Water Well Contractor's Certification:	iction and th	ie ranort ic
The state of the s	This well was drilled under my jurisd true to the best of my knowledge and bel	lief.	re refore 18
Was a drive shoe used? ★ Yes □ No Plugs Size: location ft.	Name McClanahan Well Drilling		
Did any strata contain unusable water?  Yes XXNo	(Person, firm or corporation) 141 NE Beacon Drive G	Type or rants Pas	
Type of water? depth of strata	Address TT Beacon Bive	MARI	
Method of sealing strata off	[Signed] Yourse Well	IPVa	nellen
Was well gravel packed? [] Yes NNo Size of gravel:	(Water Well Contr		
Gravel placed from ft to ft	Contractor's License No. 422 Date 0	ctober 31	. , <sub>10</sub> 78