JAN 2 1987

WATER WELL REPORT

STATE OF OREGON WATER RESOURCES DEPT.

SALEM, OREGON
PLEASE TYPE or PRINT IN INK
THEET # 1 OF 2 SHEETS

KLAMst	ate Well No	345/	8E-3fa
1064 st	ate Permit No.		

ADDRESS CONTROL OF THE PROPERTY OF THE PROPERT		····		
(1) OWNER:	(10) LOCATION OF WELL:			
Name Tim Mc Call	County Klamath Driller's well	number		
Address HC 63 Box 564 K	NE ¼ NE ¼ Section 34 T.34 S.		east	W.M.
City Chiloquin, OR. 97624 State	Tax Lot # Lot Blk		division	
(2) TYPE OF WORK (check):	Address at well location: HC 63 Box 564 K	Chilo	quin,	OR.
**	On Sprague River Hwy.			
New Well K Deepening Reconditioning Abandon	(11) WATER LEVEL: Completed w	ell.		
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found 275			ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		and surface	Date 12	23.86
Rotary Air 🛣 Driven 🗆 Domestic 🗆 Industrial 🗆 Municipal 🗆		er square in		
Mud □ Dug □ Irrigation ত Test Well □ Other □ Bored □ Thermal: Withdrawal □ Reinjection □				
		casing+	y	3 ft.
(5) CASING INSTALLED: Steel By Plastic Threaded Welded By	Depth drilled 353 ft. Depth of completed well 353 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
.10" Diam. from+1 ft. to20 ft. Gauge250				
" Diam. from				
LINER INSTALLED:	MATERIAL	From	То	CUIT
		G G	10	SWL
	Sandy top soil Yellow clay	3	13	
(6) PERFORATIONS: Perforated? □ Yes □XNo	Blue clay	13	798	2
Type of perforator used	Brown sandstone	79	102	
Size of perforations in. by in.	Blue claystone	102	141	
perforations from ft. to ft.	Brown clay	141	167	
perforations from	Yellow slay with streaks of	167	107	
perforations fromft. toft.	black sandstone	10,	190	
(7) SCREENS: Well screen installed? ☐ Yes 🕱 No	Brown claystone	190	211	
Manufacturer's Name	Blue clay	211	243	
Type Model No.	Black sandstone	243	262	
Diam. Slot Size Set from ft. to ft.	Black rock	262	268	
Diam. Slot Size Set from ft. to ft.	Black sandstone	268	275	
(8) WELL TESTS: Drawdown is amount water level is lowered below static lavel	Fractured conglomerate rock	275	290	22'
below static level	Rock conglomerate	290	296	22'
a pump test made? ☐ Yes ☑ No If yes, by whom? driller	Red and black conders	296	300	221
Yield: gal/min. with ft. drawdown after hrs.	Brown sand rock	300	302	
" " "	Red lava rock	302	314	221
Air test 600 gal./min. with drill stem at 60 ft. 1 hrs.	Black lava rock	314	329	
Bailer test gal./min. with ft. drawdown after hrs.	Brown lava rock	329	335	22
sian flow g.p.m.	CONTINUED ON ANOTHER S	HEET		
Temperature of water 54 Depth artesian flow encountered ft.	Work started 12, 17, 86 19 Complete	ed 12,2	3,86	19
(9) CONSTRUCTION: Special standards: Yes □ No 🗗	Date well drilling machine moved off of well	12,26	, 86	19
Well seal—Material usedCement	(unbonded) Water Well Constructor Certifi	ication (i	f appli	cable):
Well sealed from land surface to19 ft.	This well was constructed under my direct s	upervisio	n. Matei	rials used
Diameter of well bore to bottom of seal	and information reported above are true to my b			
Diameter of well bore below seal10 in.	[Signed]	. Date		, 19
Number of sacks of cement used in well seal	Bonded Water Well Constructor Certificati	on:		
How was cement grout placed? Pumpedfrombottomofseal.	Bond 20821134 Issued by: Wester	n Sure	ty Co).
uptotheground.surface	(number) Sur	ety Company l	Name	·-
W	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was pump installed? NO	Name Norm Sevey Well Drilling Inc.			
Was a drive shoe used? ☐ Yes ☒ No Plugs	(Person, firm or corporation) Address 5619 Leland Dr. Klamath	F2110		97603
Type of Water? depth of strata				ديوريد
Method of sealing strata off	[Signed]			***********
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	Date12	30.	86	10
Gravel placed from	Date	.g		, 15
	<u> </u>			

WATER WELL REPORT STATE OF OREGON

JAN 2 1987 WATER RESOURCES DEPT.

State Well No. 345/8E-34aa
State Permit No.

SALEM, OREGONTYPE or PRINT IN INK

1 21000	VIIIOEV			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Tim Mc Call	County Klamath Driller's well number			
Address HC 63 Box 564 K	NE 1/4 NE 1/4 Section 34 T. 34 S.R. 8 East W.M.			
City Chiloquin, OR. 97624 State	Tax Lot # Lot Blk Subdivision			
(2) TYPE OF WORK (check):	Address at well location: HC 63 Box 564 K Chiloquin, OR.			
· · · · · · · · · · · · · · · · · · ·	On Sprague River Hwy.			
New Well □ Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
	Depth at which water was first found ft.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level ft. below land surface. Date			
totary Air Driven Domestic DIndustrial Municipal Domestic Dug Test Well Other	Artesian pressure lbs. per square inch. Date			
y Mud □ Dug □ Irrigation □ Test Well □ Other □ □ Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing			
(E) CACING INCOALLED.	Depth drilled ft. Depth of completed well ft.			
(5) CASING INSTALLED: Steel	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level			
" Diam. from	and indicate principal water-bearing strata.			
LINER INSTALLED:	MATERIAL From To SWL			
"Diam. from	CONTINUED FROM SHEET # 1.			
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No Type of perforator used	Red cinders 335 349 22*			
Size of perforations in. by in.	Black rock 349 353			
perforations fromft. toft.				
perforations fromft. toft.				
perforations from				
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name				
Type Model No				
Diam. Slot Size Set from ft. to ft.				
Diam. Slot Size Set from ft. to ft.				
Drawdown is amount water level is lowered				
(8) WELL TESTS: below static level				
a pump test made? Yes No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
II " " "				
Air test gal./min. with drill stem at ft. hrs.				
Bailer test gal./min. with ft. drawdown after hrs.				
sian flow g.p.m.	10.00.06			
Temperature of water Depth artesian flow encountered ft.	Work started 12, 17, 86 19 Completed 12, 23, 86 19			
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well 12, 26, 86			
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicable):			
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore to bottom of seal in.	[Signed]			
Diameter of well bore below sealin.				
Number of sacks of cement used in well seal	Bonded Water Well Constructor Certification:			
How was cement grout placed?	Bond 20821134 Issued by: Western Surety Co. Surety Company Name			
	This well was drilled under my jurisdiction and this report is true to			
Was pump installed?	the best of my knowledge and belief. Name Norm Sevey Well Drilling, Inc.			
Was a drive shoe used? ☐ Yes ☐ No Plugs	Name Norm Sevey Well Drilling, Inc. (Person, firm or corporation) (Type or print)			
Did any strata contain unusable water? Yes No	Address 5619 Leland Dr. Klamath Falls, OR. 97603			
Type of Water? depth of strata	[Signed] Water Well Constructor			
Method of sealing strata off	Water Well Constructor Date12 3086, 19			
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Date14			
Gravel placed from ft. to ft.				