

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT NO V1 1974

FEB 18 1975 STATE OF OREGON

State Well No. 35S/6E-35cb

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

STATE ENGINEER SALEM, OREGON

(Please type or print)

STATE ENGINEER

SALEM, OREGON

State Permit No.

KLAM 1139

(1) OWNER:

Name A.R.B. INC (ROCKY POINT RESORT)
Address PO Box 1557 BAKERS FIELD, CALIF.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other [X]

CASING INSTALLED:

Threaded [] Welded [X]

6 5/8" Diam. from 3 1/2 ft. to 5.2 ft. Gage 250
" Diam. from " ft. to " ft. Gage "

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? EES
Yield: 75 gal./min. with 5 ft. drawdown after 1 hrs.
RIFT 150 " @ 40 " " " "
" 100 " @ 25 " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

(9) CONSTRUCTION:

Well seal-Material used CEMENT 1 1/2 S X MIX
Well sealed from land surface to 50 ft.
Diameter of well bore to bottom of seal 9 7/8 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 199 15 YDS SAND sacks
Number of sacks of bentonite used in well seal
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Klamath Driller's well number
NW 1/4 SW 1/4 Section 35 T. 35S R. 6R W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 29 ft.
Static level 21 ft. below land surface. Date 9/26/74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 60 ft. Depth of completed well 59 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include BROWN CLAY & BOULDERS, BLK BASALT, BRN SANDSTONE BROKEN, BLACK BASALT, BOBBY BLK LAVA.

Work started 9/17/74 19 Completed 9/26/74 19
Date well drilling machine moved off of well 9/26/74 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] David M. Hays Date 10/29, 1974
(Drilling Machine Operator)

Drilling Machine Operator's License No. 656

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name E E STOREY (Person, firm or corporation) (Type or print)

Address 3847 Hope K FALLS

[Signed] E E Storey (Water Well Contractor)

Contractor's License No. 74 Date 10/29/74, 19...

179 S. ...