NOTICE TO WATER WELL CONTRACTOR The original and first chay of this report are to be filed with the	LL REPORT	73.	19-2	7d d
STATE OF STATE ENGINEER, SALEM, OREGON 97310 EN EXPease type within 30 days from the date of well completion. SALEM OF TOO not write a	e or print) State Permit N			
(1) OWNER:	(10) LOCATION OF WELL:		·	
Name J. P. W. E. L. BORN	County/ALAMATThriller's well number			
Address 6896 S.F. MOLT	5.E. 45F. 4 Section 24 T235 R. 9 F W.M.			
MILWAUKEE ORE 972 22	Bearing and distance from section or subdivisi			
(2) TYPE OF WORK (check):				· · · · · · · · · · · · · · · · · · ·
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found / 7 ft.			
Rotary Driven Domestic Mindustrial Municipal Domestic	Static level 8 ft. below land surface. Date 4-20			
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing L			
6 "Diam. from 6 ft. to 2/ ft. Gage 1250	Depth drilled 2 / ft. Depth of completed well 2 / ft.			
"Diam from ft. to ft. Gage ft. Gage	Formation: Describe color, texture, grain size	and structu	ire of n	naterials;
	and show thickness and nature of each stratus with at least one entry for each change of forma	m and aqu	uifer pe	netrated,
Perforated? Xyes \(\square\) No.	position of Static Water Level and indicate prin	cipal wate	r-bearir	ng strata.
Type of perforator used TORCH	MATERIAL	From	То	SWL
Size of perforations /// in. by 4 in.	PUMICE	0	5	
perforations from 19 ft. to 21 ft.				·
perforations from	CLAY- GRAVEL	5	17	
perforations from ft. to ft.				
(7) SCREENS: Well screen installed? Yes No	JAND-GRAVEL	17	2/	_8
Manufacturer's Name				
Type Model No.				
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level				
Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \) No \(\text{If drawdown after} \) \(\text{brs} \)				
eld: LO gal./min. with 3 ft. drawdown after hrs.				
" " "	ž.			
" " " " " " " " " " " " " " " " " " " "	The state of the s			
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.	41.2.			
hperature of water 7 Depth artesian flow encountered ft.	Work started 4-20 1972 Complete	d 4-20	9	1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-20)	1972
Well seal-Material used BENTONITE	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my	direct s	super	vision.
Diameter of well bore to bottom of seal 6 in.	Materials used and information reported best knowledge and belief.			_
Diameter of well bore below seal in.	[Signed]	Date 4-	20	1072
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	347		, 102
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	201		**********
Brand name of bentonite YELLOWSTONE	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons of waterlbs/100 gals	This well was drilled under my jurisdiction and this report is			
of waterlbs./100 gals. Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name HARRY MAY			
Type of water? depth of strata	Address STAR RT. G-TICHRT	(Type	or prin	t)
Method of sealing strata off	Zi	<u>~./</u>		
Was well gravel packed? Yes No Size of gravel:	[Signed] / Water Well Contra	oton'		
		_		70
Gravel placed fromft. toft.	Contractor's License No. 556 Date	-0		, 19//