SALEM, OREGON 97310 within 30 days from the date of well completion.

te JUN 15 1979Please type or print)
(Do not write above this line)

State Well No. 385/9=-955
State Permit No. G-8625

Corrected by Mar-

(1) OWNER: SALEM, ORIGIN	(10) LOCATION OF WELL:
Name CURTIS T. UNDERWOOD	County KLAMATS Driller's well number
Address RT 2 Box 809C	9111 y 21014 Same 9 - 240 - 005
KLAMATH FALLS, ORE	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	bearing and distance from section of subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1
Rotary Driven Domestic Dindustrial District	Depth at which water was first found 180 ft.
Direction To Board III	Static level /D6 ft. below land surface. Date 5/22/19
	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below 15 72 75
"Diam. fromft. toft. Gage	Diameter of Well below casing 20 2020
16" OP Diam. from + 1 ft. to 26 ft. Gage 250	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? To Ves. 18 No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? Yes No. Type of perforator used	
	MATERIAL From To SWL
	BRN CAN TOPSOIL D 4
perforations fromft. toft.	YELLOW O'LLAY 4 12
perforations fromft. toft.	BROKEN BRN BASALT 12 17
	BRN 4 GRAY BASALT 17 36 GRAY BASALT 36 48
(7) SCREENS: Well screen installed? Yes No	BROKEN BRN BASALT 48 69
Manufacturer's Name	ERAY BASALT 69 87
Type Model No.	BROKEN ARAY BASALTY RED 87 85
Diam. Slot size Set from ft. to ft.	CINDERS . 91
Diam. Slot size Set from ft. to ft.	BROKEN BRN BASALT 91 118
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROKENGRAY BASALT 118 124
Was a pump test made? Yes No If yes, by whom?	BROWN BLK BASALTY BRN CINDERS 124 150
Wald.	CRAY BASALT 150 180
gar, and the state of the state	CRAYBASALTA Red CINDERS 180 255 NB
PLIFT 1000 GPM @ 610" 2"	BRN BASALT 207 325
7	CRAY BASALT 325 565
Bailer test gal./min. with ft. drawdown after hrs.	BROKEN ORAY BASHLT 565 570 WB
Artesian flow g.p.m.	GRAY BASALT 570 6/0
perature of water 5 & Depth artesian flow encountered ft.	Work started 4/4/79 19 Completed 5/22/7919
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5/32/79 19
Well seal-Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to 26 ft.	This well was constructed under my direct
Diameter of well bore to bottom of seal 20 in.	Materials used and information reported above are true to my best knowledge and belief)
Diameter of well bore below sealin.	
Jumber of sacks of cement used in well seal 3 4 sacks	(Drilling Machine Operator)
Now was cement grout placed? POURED	Drilling Machine Operator's License No. 650
A CONTRACTOR OF THE CONTRACTOR	Water Well Contractor's Certification:
The second secon	
Von a dviva akaa waada Safayaa Fili by	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Vas a drive shoe used? XYes \(\) No Plugs Size: location ft. Did any strata contain unusable water? \(\) Yes \(\) No	Name E. C. STOREY of SON WELL DAMEN, 57.18
	(Type or print)
ype of water? depth of strata	Address 39347 HOPE pk FALLS
Method of sealing strata off	[Signed]
Vas well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Fravel placed from ftlo ft.	Contractor's License No. 601 Date 6/14 19)9
400000	1