CC

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	LL REPORT		zlo	c	
WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date	e or print)	-	8		
of well completion. (Do not write a	nove uns me)				
(1) OWNER: SALEM, ORIGIN	(10) LOCATION OF WELL:				
Name CURTIS T. UNDERWOOD	l ar a				
Address RT 2 Box 809C					
KLAMATH FALLS ORE	W.M.				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner				
New Well Deepening □ Reconditioning □ Abandon □			***************************************	· · · · · · · · · · · · · · · · · · ·	
If abandonment, describe material and procedure in Item 12.			*******************		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.				
Botany W Duisson C	Depth at which water was first found 180 ft.				
Cable	Static level 106 ft. below land surface. Date 5/22/79				
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	helow cas	ina 15	to 250	
"Diam. from ft. to ft. Gage	Depth drilled 6/0 ft. Depth of comp		1941	6610	
16" OD Diam from + 1 ft. to 26 ft. Gage 250	Formation: Describe color, texture, grain size			6	
" Diam. from ft. to ft. Gage	I allo show thickness and nature of each stratu	im and a	******		
PERFORATIONS: Perforated?	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion Danc		a Year and the Paris	
Type of perforator used	MATERIAL	T		Y	
Size of perforations in. by in.	BRN CLW TOPSOIL	From	To	SWL	
perforations from ft. to ft.	VELLAN 6/1 AV		7_		
perforations from ft. to ft.	BROKEN BRN BASALT	17	12		
perforations from ft. to ft.	BRN 4 GRAY BASALT	17	36		
/ 25 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	GRAV BASALT	36	48		
(7) SCREENS: Well screen installed? Yes No	BROKEN BRN BASALT	48	69		
Manufacturer's Name	GRAY BASALT	69	27		
Type Model No.	BROKEN ARAY BASALTY REd	87	25		
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	CINDERS	•	91		
Set from ft.	BROKEN BRN BASALT	91	118		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROKENGRAY BASALT	118	124		
Was a pump test made? ☐ Yes No If yes, by whom?	BRANEN BLK BASALTY BRN CINGERS	124	50		
Viold:	GRAY BASALT GRAY BASALTY RED CINDERS	150	180		
Ins.	GRAY BASALT	4	255	NB	
BLIFT 1000 GPM @ 610" 2"	RRA RASALT	500	30%		
	GRAY BASALT	3.25	565		
Bailer test gal./min. with ft. drawdown after hrs.	BROKEN ORAY BASHLT		5/20	WB	
Artesian flow g.p.m.	GRAY BASALT	570	-10		
perature of water 5 8 Depth artesian flow encountered ft.	Work started 4/4/79 19 Complete	ed 5/	22/9	79 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5/1	3/17	9 19	
Well seal—Material used	Drilling Machine Operator's Certification:	2/2	7//		
Well sealed from land surface to 26 ft.	This well was constructed under my	direct		!!	
Diameter of well bore to bottom of seal 20 in.	Materials used and information reported best knowledge and belieff	above a	re true	to my	
Diameter of well bore below sealin.	reimand Care III The	1	. 1	777	
Number of sacks of cement used in well seal 24 sacks	[Signed] Date Oly, 19.79				
How was cement grout placed? Poured	Drilling Machine Operator's License No.	6	56	************	
, de	Wilden Will and Committee of the Committ				
*	Water Well Contractor's Certification:				
	This well was drilled under my jurisdictrue to the best of my knowledge and beli	ction and	this re	eport is	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name C. C. STOREY of SON WELL	- Dair	(n) -	150	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)		e or prin	t)	
Type of water? depth of strata	Address 39347 HOPE	100 100	ALLS	-	
Method of sealing strata off	[Signed] Signed				
Was well gravel packed? [] Yes No. Size of gravel:	[Signed] (Water Well Contra	etor)	******		
Gravel placed from ft. to ft.	Contractor's License No. 601 Date	. A.	<u>/</u>	e (01	
(USE ADDITIONAL SHI					
	- man		-SP	*4585 8- 119	

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report
are to be filed with the

STATE OF OREGON State Well No. 385/9F -9 4 JUNI 197 (Please type or print) SALEM, OREGON 97310 State Permit No. 6-8625 within 30 days from the date (Do not write above this line) of well completion. SALEM. OREGEN (10) LOCATION OF WELL: (1) OWNER: Name CURTIS T. UNGERWOOD County KLAMATh Driller's well number SW 4 SW4 Section 9 T. 385 R. 9E W.M. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well 😿 Deepening 🛚 Reconditioning [Abandon 🔲 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🛘 Domestic | Industrial | Municipal | Static level / D 6 ft. below land surface. Date Cable Jetted [] Bored 🗍 Irrigation Test Well Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded | (12) WELL LOG: Diameter of well below casing 15 to 250 "Diam. from ft. to ft. Gage 16" OP Diam. from ft. to 26 ft. Gage 25" Depth drilled 610 ft. Depth of completed well Formation: Describe color, texture, grain size and structure of materials;" Diam. from ft. to ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Tyes No. Type of perforator used MATERIAL. Size of perforations in. by in. BRN CLAY TOPSOIL 4 perforations from ft. to ft. BROKEN BRN BASALT perforations from _____ ft. to _____ ft. 17 BRN 4 GRAY BASALT perforations from ft. to ft. GRAY BASALT 36 (7) SCREENS: Well screen installed? ☐ Yes 😾 No BROKEN BRN BASAL 69 Manufacturer's Name GRAY BASALT 69 BROKEN ARAYBASILTY RED Diam. Slot size Set from CINCERS Diam. Slot size Set from ft. to _____ ft. BROKENG-RAY BASALT 118 124 Drawdown is amount water level is lowered below static level (8) WELL TESTS: BROKEN BLK BASALTY BRN CINDERS 124 150 Was a pump test made?

Yes No If yes, by whom? GRAY BASALT 150 180 180 255 FRAV BASALTY RED CINDERS gal./min. with ft. drawdown after hrs. GRAY BASALT 255 307 RLIFT 1000 GPM @ BRN BASALT 307 325 " GRAY BASALT Bailer test gal./min. with ft. drawdown after hrs. BROKEN ORAY BASALT Artesian flow 570 610 perature of water 5 & Depth artesian flow encountered Work started Completed 5/22/7919 Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal—Material used CCMENT Drilling Machine Operator's Certification: This well was constructed under my direct supervision.

Materials used and information reported above are true to my best knowledge and belief?

[Signed] Date 77 Well sealed from land surface to 26 ft. Diameter of well bore to bottom of seal 20 in. Diameter of well bore below seal (Drilling Machine Operator) Number of sacks of cement used in well seal How was cement grout placed? Poured Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name C	, C. STOREZ	1950N	WELL DA	KilNG	EN
	(Person, firm	or corporation)	('	Type or prin	t)
Address .	39:47	HOPE	nK	FALLS	
[Signed] .	Ori	£M.	flow		
·		(Water W	ell Contractor)	í	******

Contractor's License No. 601 Date 6/14 , 19)

Was a drive shoe used? Yes \(\sigma \) No Plugs Size: location ft.

depth of strata

Did any strata contain unusable water?
Yes No

Was well gravel packed? Yes No Size of gravel:

Gravel placed from _____ ft. to ____ ft.

Type of water?

Method of sealing strata off