The original and first of this report are to filed with the AUG 2 - 1972 VETER WELL REPORT OUT 1 2 197 STATE OF OREGON STATE ENGINEER Well No.

STATE ENGINEER, SALEM, CHECON ESTATE ENGINEER Well No.

STATE ENGINEER, SALEM, CHECON ESTATE ENGINEER SALEM. OF STATE ENGINEER SALEM. SALEM. OF State Polit No. (10) LOCATION OF WELL: (1) OWNER: Name Robert M. Perla County Klamath Driller's well number N.W. 14 S.E 14 Section 6 T.35S Address1922 Stradella Rd. Los Angles. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Govt, lot 14 New Well Deepening [Reconditioning [Abandon \square If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found ft. below land surface. Date 7/25/ Rotary Driven | Static level 12 Domestic 🗌 Industrial 🗌 Municipal 🗲 Cable Jetted [Irrigation | Test Well | Other Artesian pressure lbs. per square inch. Date 5) CASING INSTALLED: Threaded | Welded | Diameter of well below casing 10" (12) WELL LOG: ft. to50 ft. Gage 1 Depth drilled 326 ft. Depth of completed well 19 --- pam-non -- 324- ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials;" Diam. from .. 0 ft. to 324 ft. Gage ... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. 6) PERFORATIONS: Perforated? X Yes No. Type of perforator used Mills Knife MATERIAL From in. by 13 3/16 Size of perforations top soil Λ ... perforations from .. brown packed sand פר 210 perforations from ... yellow clay nerforations from sand & gravel 34 fine brown sand (7) SCREENS: Well screen installed? □ Yes water bearing sand & Manufacturer's Name 73 Model No. Diam. Slot size Set from ft. to layers of gray clay and sand 83 214 Diam. Slot size Set from 214 gravel and sand 220 233 black sand and gravel Drawdown is amount water level is lowered below static level valley (8) WELL TESTS: fine black sand & lavers of Was a pump test made? E Yes | No If yes, by whom pump & equip 282 gray clay 233 12 gal./min. with 138 ft. drawdown after 24 ** fine black sand & gravel 282 hrs. Bailer test 50 gal./min. with 75 ft. drawdown after Artesian flow g.p.m. 6/26 mperature of water 51 Depth artesian flow encountered ft, 1972 Completed Work started 1972 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used cement.... This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Well sealed from land surface to ____27 Diameter of well bore to bottom of seal ... 20..... in. Diameter of well bore below seal in. Date Number of sacks of cement used in well seal _______ sacks Drilling Machine Operator's License No. .. Number of sacks of bentonite used in well seal none Brand name of bentonite-and... Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is ... lbs./100 gals. true to the best of my knowledge and belief. Name John A. Van Meter Was a drive shoe used? XYes 🗌 No Plugs Size: location ... Did any strata contain unusable water? 🛣 Yes 📋 No (Person, firm or corporation) (Type or print) Type of water? surface Address P.O. Box 204 Malin, Oregon 97632 depth of strata Method of sealing strata off Cased Was well gravel packed? X Yes No Size of gravel: 1110 3/4

0 ft. to 85

Gravel placed from

Contractor's License No. 170 Date 7/27