NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORTE IVE

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGONPR 26 1973

(Please type of print E ENGINEER tate Per mit No. ... (Do not write above highling). OREGON

| (1) OWNER: | (10) LOCATION OF WELL: |
|---|--|
| Name Robert M. Perla | County Klamath Driller's well number 2 |
| Address 1922 Stradella Rd. | GOV to LOte section 6 T. 35 FR. 7 E. W.M. |
| Los Angeles, Calif. 90024 | Bearing and distance from section or subdivision corner |
| (2) TYPE OF WORK (check): | |
| New Well 🗗 Despening 🗌 Reconditioning 🗎 Abandon 🗎 | The same of the sa |
| If abandonment, describe material and procedure in Item 12, | (11) WATER LEVEL: Completed well. |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | Depth at which water was first found 135 ft. |
| Rotary Driven Domestic Industrial Municipal | 110 = 3908/72 |
| Cable 1 Jetted Domestic Industrial Industrial | |
| Dug Bored Irrigation Test Well Other | Artesian pressure lbs. per square inch. Date |
| CASING INSTALLED: 16" Diam. from 1 ft. to 63 ft. Gage 250 10" Diam. from 2 ft. to 226 ft. Gage 250 "Diam. from ft. to ft. Gage 250 PERFORATIONS: Perforated? Yes No. | (12) WELL LOG: Diameter of well below casing 10 Depth drilled 280 ft. Depth of completed well 280 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. |
| Type of perforator used Torch | MATERIAL From To SWL |
| Size of perforations 16 in. by 6 in. | Oft. 4ft. Top Soil O 4 |
| 7 rows-2 _{perforations from} 166 ft. to 226 ft. | Cemented Gravel 4 7 |
| perforations from ft. to ft. | Clay 7 21 |
| perforations fromft. toft. | Brown Shale 21 60 |
| | Brown Hard Shale 60 65 |
| (7) SCREENS: Well screen installed? ☐ Yes ☐ No | Brown Bank Sand 65 103 |
| Manufacturer's Name | Blue Clay 103 112 |
| Type Model No | 1st W. Black Sand (med) 112 114 |
| Diam. Slot size Set from ft. to ft. | Brown Sand (Cors) Sta. W. 114 136 99' |
| Diam. Slot size Set from ft. to ft. | Brown Sand (fine) 136 172 |
| (8) WELL TESTS: Drawdown is amount water level is lowered below static level | Brown Clay (packed) 172 187 |
| Was a pump test made? Yes \(\subseteq \) No If yes, by whom? Valley | Blue Clay & Rock 209 215 |
| | Lava Rock (Hard) 215 244 |
| Yield: 560 gal./min. with 81 ft. drawdown after 24 hrs. | Coarse Gravel 244 246 119' |
| " " " | Hard Rock 246 280 |
| ,, , , , , , , , , , , , , , , , , , , | 2.0 2.0 |
| Bailer test 100 gal./min. with not. drawdown after hrs. | garan and an analysis of the state of the st |
| Artesian flow g.p.m. | # |
| perature of water Depth artesian flow encountered ft. | Work started Feb 5 1973 Completed Apr. 3 1973 |
| (9) CONSTRUCTION: | Date well drilling machine moved off of well A pr. 3 1973 |
| Well seal—Material used Cement | Drilling Machine Operator's Certification: |
| Well sealed from land surface to 62 ft. Diameter of well bore to bottom of seal 20 in. Diameter of well bore below seal 12 in. | This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief [Signed] Date Apr. 17, 173 |
| Number of sacks of centent used in wen sear and an analysis sacks | Drilling Machine Operator's License No. 2333 |
| Number of sacks of bentonite used in well seal HOHE sacks Brand name of bentonite | |
| | Water Well Contractor's Certification: |
| Number of pounds of bentonite per 100 gallons of water lbs_/100 gals. | This well was drilled under my jurisdiction and this report is |
| Was a drive shoe used? Yes No Plugs Size: location ft. | true to the best of my knowledge and belief. Name Charles E. Hartley Welldrilling |
| Did any strata contain unusable water? 🗆 Yes 🛅 No | Name CHARTLES E. HATTLEY Welldrilling (Person, firm or corporation) (Type or print) |
| Type of water? depth of strata | Address 4779 South Sixth St |
| Method of sealing strata off | [Signed] Klada to Talls, Oregon 97601 |
| Was well gravel packed ▼ ☐ Yes ☐ No Size of gravel: | (Water Well Contractor) |
| Gravel placed from O ft. to 140 ft. | Contractor's License No. 145 Date Abr. 17 , 1973 |